




## List 10051

EXOTAP® VCX V-XPM-HT

STRAIGHT FLUTE	XPM	V	C/2.5P	0°	PACKED 1 PIECE
----------------	-----	---	--------	----	-------------------



EDP		Thread Size	Thread Limit	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Number of Flutes
				L (Inch)	Lc (Inch)	L1 (Inch)	d (Inch)	k (Inch)	lk (Inch)	
1005110508	●	No. 6 - 32 UNC	H3	2.000	0.374	0.688	0.141	0.110	0.188	4
1005110808	●	No. 8 - 32 UNC	H3	2.125	0.374	0.751	0.168	0.131	0.250	4
1005111008	●	No. 10 - 24 UNC	H3	2.375	0.500	0.874	0.194	0.152	0.250	4
1005111208	●	No. 10 - 32 UNF	H3	2.375	0.500	0.874	0.194	0.152	0.250	4
1005111408	●	1/4 - 20 UNC	H5	2.500	0.598	1.000	0.255	0.191	0.313	4
1005111608	●	1/4 - 28 UNF	H4	2.500	0.586	0.988	0.255	0.191	0.313	4
1005111808	●	5/16 - 18 UNC	H5	2.719	0.665	1.125	0.318	0.238	0.375	5
1005112008	●	5/16 - 24 UNF	H4	2.719	0.665	1.125	0.318	0.238	0.375	5
1005112208	●	3/8 - 16 UNC	H5	2.938	0.751	1.251	0.381	0.286	0.438	5
1005112408	●	3/8 - 24 UNF	H4	2.938	0.751	1.251	0.381	0.286	0.438	5
1005113008	●	1/2 - 13 UNC	H5	3.375	0.921	1.933	0.367	0.275	0.438	5
1005113208	●	1/2 - 20 UNF	H5	3.375	0.921	1.933	0.367	0.275	0.438	5
1005113408	●	9/16 - 12 UNC	H5	3.594	1.000	1.972	0.429	0.322	0.500	5
1005113608	●	9/16 - 18 UNF	H5	3.594	1.000	1.972	0.429	0.322	0.500	5
1005113808	●	5/8 - 11 UNC	H6	3.813	1.091	2.126	0.480	0.360	0.563	5
1005114008	●	5/8 - 18 UNF	H5	3.813	1.091	2.126	0.480	0.360	0.563	5
1005114208	●	3/4 - 10 UNC	H6	4.250	1.201	2.433	0.590	0.442	0.688	5
1005114408	●	3/4 - 16 UNF	H5	4.250	1.201	2.433	0.590	0.442	0.688	5
1005114608	●	7/8 - 9 UNC	H7	4.688	1.335	2.654	0.697	0.523	0.750	5
1005114808	●	7/8 - 14 UNF	H6	4.688	1.335	2.654	0.697	0.523	0.750	5
1005115008	●	1 - 8 UNC	H7	5.125	1.500	3.012	0.800	0.600	0.813	5
1005115208	●	1 - 12 UNF	H6	5.125	1.500	3.012	0.800	0.600	0.813	5

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H					
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel					
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium						
Low	Medium	High							6061	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
1010	1035	1065	4140	○	300	400	17-4 PH		6061									
1018	1045		4340						7075									
			15-20 SFM															

○ Good ⊗ Best

