




## List 10057

EXOTAP® DC-OIL VPO-DC-HT

STRAIGHT FLUTE	VC10	V	4 FLUTE	C/1.5P	0°	PACKED 1 PIECE
----------------	------	---	---------	--------	----	----------------



EDP	Thread Size	Thread Limit	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	
			L (Inch)	Lc (Inch)	L1 (Inch)	d (Inch)	k (Inch)	lk (Inch)	
1005700108	●	1/4 - 20 UNC	H3	2.500	0.598	1.000	0.255	0.191	0.313
1005700208	●	1/4 - 20 UNC	H5	2.500	0.598	1.000	0.255	0.191	0.313
1005700308	●	1/4 - 28 UNF	H3	2.500	0.598	1.000	0.255	0.191	0.313
1005700408	●	5/16 - 18 UNC	H3	2.719	0.665	1.125	0.318	0.238	0.375
1005700508	●	5/16 - 18 UNC	H5	2.719	0.665	1.125	0.318	0.238	0.375
1005700608	●	5/16 - 24 UNF	H3	2.719	0.665	1.125	0.318	0.238	0.375
1005700708	●	3/8 - 16 UNC	H3	2.938	0.751	1.251	0.381	0.286	0.438
1005700808	●	3/8 - 16 UNC	H5	2.938	0.751	1.251	0.381	0.286	0.438
1005700908	●	3/8 - 24 UNF	H3	2.938	0.751	1.251	0.381	0.286	0.438
1005701008	●	7/16 - 14 UNC	H3	3.156	0.858	1.712	0.323	0.242	0.406
1005701108	●	7/16 - 14 UNC	H5	3.156	0.858	1.712	0.323	0.242	0.406
1005701208	●	7/16 - 20 UNF	H3	3.156	0.858	1.712	0.323	0.242	0.406
1005701308	●	7/16 - 20 UNF	H5	3.156	0.858	1.712	0.323	0.242	0.406
1005701408	●	1/2 - 13 UNC	H3	3.375	0.921	1.933	0.367	0.275	0.438
1005701508	●	1/2 - 13 UNC	H5	3.375	0.921	1.933	0.367	0.275	0.438
1005701608	●	1/2 - 20 UNF	H3	3.375	0.921	1.933	0.367	0.275	0.438
1005701708	●	1/2 - 20 UNF	H5	3.375	0.921	1.933	0.367	0.275	0.438

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

EXT

P					M			K	N		S		H						
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel						
Carbon Steel			Alloy Steel	Die Steel			Aluminum		Nickel Alloy	Titanium									
Low	Medium	High			300	400	17-4 PH				6061	Casting	Inconel	6Al4V	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC	
1010	1035	1065	4140	4340															
1018	1045							○		○									
								40-100 SFM		50-110 SFM									

○ Good ⊙ Best

