




## List 10059

EXOCARB® CHT

STRAIGHT FLUTE	CARBIDE	BR	4 FLUTE	C/1.5P	0°	PACKED
						1 PIECE



EDP	Thread Size	Class of Fit	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	
			L (Inch)	Lc (Inch)	L1 (Inch)	d (Inch)	k (Inch)	lk (Inch)	
1005910100	●	No. 10 - 24 UNC	2B	2.375	0.492	0.866	0.194	0.152	0.250
1005910200	●	No. 10 - 32 UNF	2B	2.375	0.500	0.874	0.194	0.152	0.250
1005910300	●	No. 12 - 24 UNC	2B	2.375	0.496	0.933	0.220	0.165	0.281
1005910400	●	1/4 - 20 UNC	2B	2.500	0.594	0.996	0.255	0.191	0.313
1005910500	●	1/4 - 28 UNF	2B	2.500	0.606	1.007	0.255	0.191	0.313
1005910600	●	5/16 - 18 UNC	2B	2.719	0.665	1.125	0.318	0.238	0.375
1005910700	●	5/16 - 24 UNF	2B	2.719	0.665	1.125	0.318	0.238	0.375
1005910800	●	3/8 - 16 UNC	2B	2.938	0.751	1.251	0.381	0.286	0.438
1005910900	●	3/8 - 24 UNF	2B	2.938	0.751	1.251	0.381	0.286	0.438

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked  
 Note: Other coatings are available upon request.



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

P					M			K	N			S		Other			
Steel					Stainless Steel			Cast Iron	Non-Ferrous			HRSA		Fiberglass	Cobalt-Chrome	Thermo-Plastics	Thermo-setting Plastics
Carbon Steel			Alloy Steel	Die Steel	300	400	17-4 PH		Aluminum	MMC (Metal Matrix Composites)	Copper Alloys	Nickel Alloy	Titanium				
Low	Medium	High															
1010	1035	1065	4140	4340				6061	7075	Casting	Inconel	6A14V					
								○	○	○			○	○			
								40-90 SFM	60-160 SFM	55-120 SFM			40-80 SFM		30-60 SFM	15-40 SFM	

○ Good ○ Best

