

## List 11016

HY-PRO® AL-DIN-POT, DIN Overall Length

SPIRAL POINT	HSSE	N	C/4P	0°	PACKED 1 PIECE
--------------	------	---	------	----	-------------------



EDP		Thread Size	Thread Limit	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Number of Flutes
				L (Inch)	Lc (Inch)	L1 (Inch)	d (Inch)	k (Inch)	lk (Inch)	
1101600103	●	No. 2 - 56 UNC	H2	1.772	0.437	0.476	0.141	0.110	0.188	2
1101600203	●	No. 4 - 40 UNC	H2	2.201	0.295	0.705	0.141	0.110	0.188	2
1101600303	●	No. 6 - 32 UNC	H3	2.201	0.370	0.783	0.141	0.110	0.188	3
1101600403	●	No. 8 - 32 UNC	H3	2.480	0.374	0.827	0.168	0.131	0.250	3
1101600503	●	No. 10 - 24 UNC	H3	2.748	0.492	1.059	0.194	0.152	0.250	3
1101600603	●	No. 10 - 32 UNF	H3	2.748	0.492	0.984	0.194	0.152	0.250	3
1101600703	●	1/4 - 20 UNC	H3	3.146	0.594	1.177	0.255	0.191	0.313	3
1101600803	●	1/4 - 20 UNC	H5	3.146	0.594	1.177	0.255	0.191	0.313	3
1101600903	●	1/4 - 28 UNF	H3	3.146	0.594	1.189	0.255	0.191	0.313	3
1101601003	●	5/16 - 18 UNC	H3	3.677	0.799	1.512	0.318	0.238	0.375	3
1101601103	●	5/16 - 18 UNC	H5	3.677	0.799	1.512	0.318	0.238	0.375	3
1101601203	●	5/16 - 24 UNF	H3	3.677	0.799	1.520	0.318	0.238	0.375	3
1101601303	●	3/8 - 16 UNC	H3	4.102	0.917	1.543	0.381	0.286	0.438	3
1101601403	●	3/8 - 16 UNC	H5	4.102	0.917	1.555	0.381	0.286	0.438	3
1101601503	●	3/8 - 24 UNF	H3	4.102	0.917	1.555	0.381	0.286	0.438	3
1101601603	●	7/16 - 14 UNC	H3	3.937	0.858	1.291	0.323	0.242	0.406	3
1101601703	●	7/16 - 14 UNC	H5	3.937	0.858	1.291	0.323	0.242	0.406	3
1101601803	●	7/16 - 20 UNF	H3	3.937	0.858	1.291	0.323	0.242	0.406	3
1101601903	●	1/2 - 13 UNC	H3	4.221	0.921	1.354	0.367	0.275	0.438	3
1101602003	●	1/2 - 13 UNC	H5	4.331	0.921	1.354	0.367	0.275	0.438	3
1101602103	●	1/2 - 20 UNF	H3	3.937	0.921	1.354	0.367	0.275	0.438	3

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium				
Low	Medium	High			6061	7075	Casting		Inconel	6Al4V (30 HRC)						
1010	1035	1065	4140	4340	300	400	17-4 PH		⊙	⊙			~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
1018	1045								⊙	⊙						
									40-80 SFM	40-65 SFM						

○ Good ⊙ Best

