




List 11051

EXOTAP® VCX V-XPM-HT

STRAIGHT FLUTE	XPM	V	C/2.5P	0°	PACKED 1 PIECE
----------------	-----	---	--------	----	-------------------



EDP		Thread Size	Thread Limit	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Number of Flutes
				L (mm)	Lc (mm)	L1 (mm)	d (mm)	k (mm)	lk (mm)	
1105100108	●	M3 x 0.5	D3	49.20	6.20	16.10	3.58	2.79	4.76	4
1105100208	●	M4 x 0.7	D4	54.00	8.40	19.10	4.27	3.33	6.35	4
1105100308	●	M5 x 0.8	D4	60.30	9.60	22.20	4.93	3.86	6.35	4
1105100408	●	M6 x 1	D5	63.00	12.00	25.40	6.48	4.85	7.94	4
1105100608	●	M8 x 1	D5	69.10	15.00	28.60	8.08	6.05	9.53	5
1105100508	●	M8 x 1.25	D5	69.10	15.00	28.60	8.08	6.05	9.53	5
1105100908	●	M10 x 1	D5	74.60	18.00	31.80	9.68	7.26	11.11	5
1105100808	●	M10 x 1.25	D5	74.60	18.00	31.80	9.68	7.26	11.11	5
1105100708	●	M10 x 1.5	D6	74.60	18.00	31.80	9.68	7.26	11.11	5
1105101208	●	M12 x 1.25	D6	85.70	21.00	49.10	9.32	6.99	11.11	5
1105101108	●	M12 x 1.5	D6	85.70	21.00	49.10	9.32	6.99	11.11	5
1105101008	●	M12 x 1.75	D6	85.70	21.00	49.10	9.32	6.99	11.11	5
1105101408	●	M14 x 1.5	D6	91.30	24.00	50.10	10.90	8.18	12.70	5
1105101308	●	M14 x 2	D7	91.30	24.00	50.10	10.90	8.18	12.70	5
1105101608	●	M16 x 1.5	D6	96.80	24.00	54.00	12.19	9.14	14.29	5
1105101508	●	M16 x 2	D7	96.80	24.00	54.00	12.19	9.14	14.29	5
1105101808	●	M18 x 1.5	D6	102.40	30.00	55.00	13.77	10.31	15.88	5
1105101708	●	M18 x 2.5	D7	102.40	30.00	55.00	13.77	10.31	15.88	5
1105102008	●	M20 x 1.5	D6	113.50	30.00	61.80	16.56	12.42	17.46	5
1105101908	●	M20 x 2.5	D7	113.50	30.00	61.80	16.56	12.42	17.46	5
1105102208	●	M22 x 1.5	D6	119.10	30.00	67.40	17.70	13.28	19.05	5
1105102108	●	M22 x 2.5	D7	119.10	30.00	67.40	17.70	13.28	19.05	5
1105102408	●	M24 x 1.5	D6	124.60	36.00	68.40	19.30	14.48	19.05	5
1105102308	●	M24 x 3	D8	124.60	36.00	68.40	19.30	14.48	19.05	5

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H					
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel					
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium						
Low	Medium	High							6061	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
1010	1035	1065	4140	15-20 SFM	300	400	17-4 PH		6061									
1018	1045		4340						7075									

○ Good ⊙ Best

