




List 11057

EXOTAP® DC-OIL VPO-DC-HT



EDP	Thread Size	Thread Limit	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Number of Flutes
			L (mm)	Lc (mm)	L1 (mm)	d (mm)	k (mm)	lk (mm)	
1105700108	M6 x 1	D5	63.50	12.00	25.40	6.48	4.85	7.94	3
1105700208	M8 x 1.25	D5	69.10	15.00	28.60	8.08	6.05	9.53	4
1105700308	M10 x 1.25	D6	74.60	18.00	31.80	9.68	7.26	11.11	4
1105700408	M10 x 1.5	D6	74.60	18.00	31.80	9.68	7.26	11.11	4
1105700508	M12 x 1.5	D6	85.70	21.00	49.10	9.32	6.99	11.11	4
1105700608	M12 x 1.75	D6	85.70	21.00	49.10	9.32	6.99	11.11	4
1105700708	M14 x 1.5	D7	91.30	24.00	50.10	10.90	8.18	12.70	5
1105700808	M14 x 2	D7	91.30	24.00	50.10	10.90	8.18	12.70	5

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

EXT

P					M			K	N		S		H				
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel				
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium					
Low	Medium	High							6061	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC
1010	1035	1065	4140	4340	300	400	17-4 PH	○	○								
1018	1045							40-100 SFM	50-110 SFM								

○ Good ○ Best

