



## List 11117

HY-PRO® V-DIN-POT, DIN Overall Length

SPIRAL POINT	HSSE	V	3 FLUTE	C/4P	0°	PACKED 1 PIECE
--------------	------	---	---------	------	----	-------------------



EDP	Thread Size	Thread Limit	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length
			L (mm)	Lc (mm)	L1 (mm)	d (mm)	k (mm)	lk (mm)
1111700108	M3 x 0.5	D3	56.00	6.30	18.30	3.58	2.79	4.76
1111700308	M4 x 0.7	D4	63.00	8.60	21.20	4.27	3.33	6.35
1111700408	M5 x 0.8	D4	70.00	9.80	25.20	4.93	3.86	6.35
1111700508	M6 x 1	D5	80.00	12.20	30.20	6.48	4.85	7.94
1111700808	M8 x 1.25	D5	90.00	15.20	35.20	8.08	6.05	9.53
1111701008	M10 x 1.5	D6	100.00	18.20	39.20	9.68	7.26	11.11
1111701308	M12 x 1.75	D6	100.00	21.90	32.00	9.32	6.99	11.11

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium				
Low	Medium	High			300	400	17-4 PH		6061	Casting			Inconel	6Al4V	~35 HRC	35-45 HRC
1010	1035	1065	4140	4340	300	400	17-4 PH	6061	7075	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
○	○	○	○	○	○	○	○	○					○			
50-90 SFM	40-80 SFM	40-60 SFM	40-80 SFM	20-60 SFM	40-80 SFM	40-80 SFM	30-50 SFM	30-80 SFM					20-60 SFM			

○ Good ○ Best

