



List 13063

EXOPRO[®] Ti V-CPM-RFT, RHC/LHS for Through Hole

SPIRAL FLUTE	VC10	V	C/4.5P	21°	LH	PACKED 1 PIECE
--------------	------	---	--------	-----	----	-------------------



EDP Number	Thread Size	Thread Limit	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Number of Flutes	
			L (Inch)	Lc (Inch)	L1 (Inch)	d (Inch)	k (Inch)	lk (Inch)		
1306300108	●	No. 2 - 56 UNC	H2	1.752	0.437	0.476	0.141	0.110	0.188	2
1306300208	●	No. 4 - 40 UNC	H2	1.874	0.295	0.560	0.141	0.110	0.188	3
1306300308	●	No. 6 - 32 UNC	H3	2.000	0.370	0.685	0.141	0.110	0.188	3
1306300408	●	No. 8 - 32 UNC	H3	2.126	0.374	0.752	0.168	0.131	0.250	3
1306300508	●	No. 10 - 24 UNC	H3	2.374	0.492	0.866	0.194	0.152	0.250	3
1306300608	●	No. 10 - 32 UNF	H3	2.374	0.492	0.866	0.194	0.152	0.250	3
1306300708	●	1/4 - 20 UNC	H3	2.500	0.594	0.997	0.255	0.191	0.313	3
1306300808	●	1/4 - 20 UNC	H5	2.500	0.594	0.997	0.255	0.191	0.313	3
1306300908	●	1/4 - 28 UNF	H3	2.500	0.594	0.997	0.255	0.191	0.313	3
1306301008	●	5/16 - 18 UNC	H3	2.720	0.665	1.126	0.318	0.238	0.375	3
1306301108	●	5/16 - 18 UNC	H5	2.720	0.665	1.126	0.318	0.238	0.375	3
1306301208	●	5/16 - 24 UNF	H3	2.720	0.665	1.126	0.318	0.238	0.375	3
1306301308	●	3/8 - 16 UNC	H3	2.937	0.752	1.252	0.381	0.286	0.438	3
1306301408	●	3/8 - 16 UNC	H5	2.937	0.752	1.252	0.381	0.286	0.438	3
1306301508	●	3/8 - 24 UNF	H3	2.937	0.752	1.252	0.381	0.286	0.438	3
1306301608	●	7/16 - 14 UNC	H3	3.157	0.858	1.291	0.323	0.242	0.406	3
1306301708	●	7/16 - 20 UNF	H3	3.157	0.858	1.291	0.323	0.242	0.406	3
1306301808	●	1/2 - 13 UNC	H3	3.374	0.921	1.354	0.367	0.275	0.438	3
1306301908	●	1/2 - 13 UNC	H5	3.374	0.921	1.354	0.367	0.275	0.438	3
1306302008	●	1/2 - 20 UNF	H3	3.374	0.921	1.354	0.367	0.275	0.438	3

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

P					M			K	N		S		H				
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel				
Carbon Steel			Alloy Steel	Die Steel	Aluminum		Nickel Alloy		Titanium								
Low	Medium	High			6061	7075				Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC	
1010	1035	1065	4140	○	300	400	17-4 PH	○	6061	7075	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
1018	1045	1065	4340		300	400	17-4 PH		6061	7075	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
			15-50 SFM				8-20 SFM					8-20 SFM	15-35 SFM				

○ Good ⊗ Best

