



HY-PRO® HXL-W-OIL

Ideal for Wind Energy Applications

ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

List 13126

HY-PRO® HXL-W-OIL-SFT, Horizontal Applications, DIN Overall Length



EDP Number	Thread Size	Thread Limit	Overall Length			Shank Diameter	Square Width	Square Length	Number of Flutes
			L (mm)	Lc (mm)	L1 (mm)				
1312602401	M16 x 2	D7	110.00	16.00	58.00	12.19	9.14	14.29	4
1312602501	M16 x 2	D7	180.00	16.00	96.00	12.19	9.14	14.29	4
1312602301	M16 x 2	D17 (6H +0.005")	110.00	16.00	58.00	12.19	9.14	14.29	4
1312600201	M20 x 2.5	D8	200.00	20.00	103.00	16.56	12.42	17.46	4
1312600101	M20 x 2.5	D8	140.00	20.00	73.00	16.56	12.42	17.46	4
1312601601	M20 x 2.5	D18 (6H +0.005")	140.00	20.00	73.00	16.56	12.42	17.46	4
1312600501	M24 x 3	D9	200.00	24.00	108.00	19.30	14.48	19.05	5
1312600401	M24 x 3	D9	160.00	24.00	88.00	19.30	14.48	19.05	5
1312601701	M24 x 3	D19 (6H +0.005")	160.00	24.00	88.00	19.30	14.48	19.05	5
1312600701	M27 x 3	D9	200.00	24.00	108.00	22.76	17.07	22.23	5
1312600601	M27 x 3	D9	160.00	24.00	88.00	22.76	17.07	22.23	5
1312601801	M27 x 3	D19 (6H +0.005")	160.00	24.00	88.00	22.76	17.07	22.23	5
1312600801	M30 x 3.5	D10	180.00	28.00	103.00	25.93	19.46	25.40	5
1312600901	M30 x 3.5	D10	250.00	28.00	138.00	25.93	19.46	25.40	5
1312601901	M30 x 3.5	D20 (6H +0.005")	180.00	28.00	103.00	25.93	19.46	25.40	5
1312601001	M33 x 3.5	D10	180.00	28.00	93.00	28.14	21.11	26.99	5
1312601101	M33 x 3.5	D10	250.00	28.00	128.00	28.14	21.11	26.99	5
1312602001	M33 x 3.5	D20 (6H +0.005")	180.00	28.00	93.00	28.14	21.11	26.99	5
1312601201	M36 x 4	D11	200.00	32.00	118.00	31.32	23.50	28.58	5
1312601301	M36 x 4	D11	250.00	32.00	143.00	31.32	23.50	28.58	5
1312602101	M36 x 4	D21 (6H +0.005")	200.00	32.00	118.00	31.32	23.50	28.58	5
1312601401	M42 x 4.5	D11	200.00	36.00	98.00	36.32	27.23	31.75	6
1312601501	M42 x 4.5	D11	300.00	36.00	148.00	36.32	27.23	31.75	6
1312602201	M42 x 4.5	D21 (6H +0.005")	200.00	36.00	98.00	36.32	27.23	31.75	6

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel	300	400	17-4 PH		Aluminum		Nickel Alloy	Titanium	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
Low	Medium	High							6061	Casting						
1010	1035	1065	4140					○	○	○	○					
1018	1045		4340		○	○	○	○					○	○		
50-120 SFM	45-110 SFM	40-100 SFM	45-110 SFM	20-60 SFM	30-70 SFM	30-70 SFM	20-50 SFM	40-100 SFM					20-60 SFM	15-50 SFM		

○ Good ○ Best

