



List 15010

OSG DCT75

HSS

TiN

PACKED
1 PIECE

EDP Number		Thread Size	Thread Length	Shank Diameter
			Lc (mm)	d (mm)
1501000105	●	M3 x 0.5	5.00	6.00
1501000205	●	M4 x 0.7	5.00	6.00
9342019	●	M6 x 1	6.20	10.00
9342021	●	M8 x 1	6.20	10.00
9342020	●	M8 x 1.25	7.30	10.00
9342022	●	M10 x 1.5	8.30	10.00
9342025	●	M12 x 1.75	9.70	12.00
9342027	●	M16 x 1.5	8.70	16.00

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

Note: Since it is made to measure class 6H, it can also be used as is for 4H, 5H, JIS I and JIS II. If the internal thread is a blind hole, please confirm that the internal thread length is longer than the screw length of DCT75. The selection of the Height Master is required if the nominal diameter of the internal thread has a chamfer or counterbore over 1.5mm. Please consult with your local sales representative.

EXT

Sleeve and Height Master Selection Chart

Shank Diameter	Metric Sizes	Sleeve Hole Dia.	Height Master Dia.
6mm	M3 - M4	6.5mm	6mm
10mm - 16mm	M6 - M16	17.5mm (included with the Digimatic Indicator)	16mm

