



List 15015

OSG DCT75

HSS

TiN

PACKED

1 PIECE



EDP Number		Thread Size	Thread Length	Shank Diameter
			Lc (mm)	d (mm)
1501500105	●	No. 5 - 44 UNF	5.00	6.00
1501500205	●	No. 6 - 32 UNC	5.00	6.00
1501500305	●	No. 10 - 24 UNC	5.90	6.00
1501500405	●	No. 10 - 32 UNF	5.00	6.00
9342028	●	1/4 - 20 UNC	7.00	10.00
9342029	●	1/4 - 28 UNF	5.00	10.00
1501500505	●	1/4 - 32 UNEF	5.00	10.00
9342030	●	5/16 - 18 UNC	7.80	10.00
9342031	●	5/16 - 24 UNF	7.00	10.00
9342033	●	3/8 - 16 UNC	8.80	10.00
9342034	●	3/8 - 24 UNF	7.00	10.00
9342035	●	7/16 - 14 UNC	10.00	12.00
9342036	●	7/16 - 20 UNF	7.00	12.00
9342037	●	1/2 - 13 UNC	10.80	13.00
9342038	●	1/2 - 20 UNF	7.00	13.00
1501500605	●	1/2 - 32 UN	5.00	13.00
1501500705	●	9/16 - 18 UNF	7.80	15.00
1501500805	●	5/8 - 11 UNC	12.70	16.00
1501500905	●	5/8 - 18 UNF	7.80	16.00
1501501005	●	3/4 - 10 UNC	14.00	20.00
1501501105	●	3/4 - 16 UNF	8.80	20.00
1501501205	●	7/8 - 9 UNC	15.60	23.00
1501501305	●	7/8 - 14 UNF	10.00	23.00
1501501405	●	1 - 8 UNC	17.50	25.50
1501501505	●	1 - 12 UNF	11.70	25.50

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

Note: Since it is made to measure class 2B, it can also be used as is for 3B. If the internal thread is a blind hole, please confirm that the internal thread length is longer than the screw length of DCT75. The selection of the Height Master is required if the nominal diameter of the internal thread has a chamfer or counterbore over 1.5mm. Please consult with your local sales representative.

EXT

Sleeve and Height Master Selection Chart

Shank Diameter	Inch Sizes	Sleeve Hole Dia.	Height Master Dia.
6mm	No. 5 - No.10	6.5mm	6mm
10mm - 16mm	1/4" - 5/8"	17.5mm (included with the Digimatic Indicator)	16mm
20mm - 25.5mm	3/4" - 1	26.5mm	

