



List 16050

EXOPRO® OIL-S-XPF, DIN Overall Length



FORMING HSS-Co V C/1.5P C/2.5P C/4.5P PACKED 1 PIECE



EDP Number	Thread Size	Thread Limit	Chamfer Type	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Tap Drill Size	
				L (Inch)	Lc (Inch)	L1 (Inch)	d (Inch)	k (Inch)	lk (Inch)	Min (Inch)	Max (Inch)
1605014204	1/4 - 20 UNC	H4	Modified Bottom (2.5P)	3.150	0.500	1.181	0.255	0.191	0.313	0.225	0.230
1605014216	1/4 - 20 UNC	H6	Bottom (1.5P)	3.150	0.500	1.181	0.255	0.191	0.313	0.225	0.230
1605014206	1/4 - 20 UNC	H6	Modified Bottom (2.5P)	3.150	0.500	1.181	0.255	0.191	0.313	0.225	0.230
1605014246	1/4 - 20 UNC	H6	Plug (4.5P)	3.150	0.500	1.181	0.255	0.191	0.313	0.225	0.230
1605014284	1/4 - 28 UNF	H4	Modified Bottom (2.5P)	3.150	0.500	1.181	0.255	0.191	0.313	0.232	0.235
1605014816	1/4 - 28 UNF	H6	Bottom (1.5P)	3.150	0.500	1.181	0.255	0.191	0.313	0.232	0.235
1605014286	1/4 - 28 UNF	H6	Modified Bottom (2.5P)	3.150	0.500	1.181	0.255	0.191	0.313	0.232	0.235
1605014846	1/4 - 28 UNF	H6	Plug (4.5P)	3.150	0.500	1.181	0.255	0.191	0.313	0.232	0.235
1605056185	5/16 - 18 UNC	H5	Modified Bottom (2.5P)	3.543	0.555	1.378	0.318	0.238	0.375	0.284	0.290
1605051617	5/16 - 18 UNC	H7	Bottom (1.5P)	3.543	0.555	1.378	0.318	0.238	0.375	0.284	0.290
1605056187	5/16 - 18 UNC	H7	Modified Bottom (2.5P)	3.543	0.555	1.378	0.318	0.238	0.375	0.284	0.290
1605051647	5/16 - 18 UNC	H7	Plug (4.5P)	3.543	0.555	1.378	0.318	0.238	0.375	0.284	0.290
1605056245	5/16 - 24 UNF	H5	Modified Bottom (2.5P)	3.543	0.555	1.378	0.318	0.238	0.375	0.291	0.296
1605056217	5/16 - 24 UNF	H7	Bottom (1.5P)	3.543	0.555	1.378	0.318	0.238	0.375	0.291	0.296
1605056247	5/16 - 24 UNF	H7	Modified Bottom (2.5P)	3.543	0.555	1.378	0.318	0.238	0.375	0.291	0.296
1605056447	5/16 - 24 UNF	H7	Plug (4.5P)	3.543	0.555	1.378	0.318	0.238	0.375	0.291	0.296
1605038165	3/8 - 16 UNC	H5	Modified Bottom (2.5P)	3.937	0.626	1.575	0.381	0.286	0.438	0.343	0.350
1605038117	3/8 - 16 UNC	H7	Bottom (1.5P)	3.937	0.626	1.575	0.381	0.286	0.438	0.343	0.350
1605038167	3/8 - 16 UNC	H7	Modified Bottom (2.5P)	3.937	0.626	1.575	0.381	0.286	0.438	0.343	0.350
1605038147	3/8 - 16 UNC	H7	Plug (4.5P)	3.937	0.626	1.575	0.381	0.286	0.438	0.343	0.350
1605038245	3/8 - 24 UNF	H5	Modified Bottom (2.5P)	3.937	0.626	1.575	0.381	0.286	0.438	0.354	0.358
1605038217	3/8 - 24 UNF	H7	Bottom (1.5P)	3.937	0.626	1.575	0.381	0.286	0.438	0.354	0.358
1605038247	3/8 - 24 UNF	H7	Modified Bottom (2.5P)	3.937	0.626	1.575	0.381	0.286	0.438	0.354	0.358
1605038447	3/8 - 24 UNF	H7	Plug (4.5P)	3.937	0.626	1.575	0.381	0.286	0.438	0.354	0.358
1605076145	7/16 - 14 UNC	H5	Modified Bottom (2.5P)	3.937	0.713	1.713	0.323	0.242	0.406	0.401	0.408
1605076118	7/16 - 14 UNC	H8	Bottom (1.5P)	3.937	0.713	1.713	0.323	0.242	0.406	0.401	0.408
1605076148	7/16 - 14 UNC	H8	Modified Bottom (2.5P)	3.937	0.713	1.713	0.323	0.242	0.406	0.401	0.408
1605076448	7/16 - 14 UNC	H8	Plug (4.5P)	3.937	0.713	1.713	0.323	0.242	0.406	0.401	0.408
1605076205	7/16 - 20 UNF	H5	Modified Bottom (2.5P)	3.937	0.713	1.713	0.323	0.242	0.406	0.412	0.417
1605076218	7/16 - 20 UNF	H8	Bottom (1.5P)	3.937	0.713	1.713	0.323	0.242	0.406	0.412	0.417
1605076208	7/16 - 20 UNF	H8	Modified Bottom (2.5P)	3.937	0.713	1.713	0.323	0.242	0.406	0.412	0.417
1605076248	7/16 - 20 UNF	H8	Plug (4.5P)	3.937	0.713	1.713	0.323	0.242	0.406	0.412	0.417
1605012135	1/2 - 13 UNC	H5	Modified Bottom (2.5P)	4.331	0.768	1.933	0.367	0.275	0.438	0.461	0.469
1605012118	1/2 - 13 UNC	H8	Bottom (1.5P)	4.331	0.768	1.933	0.367	0.275	0.438	0.461	0.469
1605012138	1/2 - 13 UNC	H8	Modified Bottom (2.5P)	4.331	0.768	1.933	0.367	0.275	0.438	0.461	0.469
1605012148	1/2 - 13 UNC	H8	Plug (4.5P)	4.331	0.768	1.933	0.367	0.275	0.438	0.461	0.469
1605012205	1/2 - 20 UNF	H5	Modified Bottom (2.5P)	3.937	0.768	1.933	0.367	0.275	0.438	0.475	0.480
1605012218	1/2 - 20 UNF	H8	Bottom (1.5P)	3.937	0.768	1.933	0.367	0.275	0.438	0.475	0.480
1605012208	1/2 - 20 UNF	H8	Modified Bottom (2.5P)	3.937	0.768	1.933	0.367	0.275	0.438	0.475	0.480
1605012248	1/2 - 20 UNF	H8	Plug (4.5P)	3.937	0.768	1.933	0.367	0.275	0.438	0.475	0.480
1605096127	9/16 - 12 UNC	H7	Modified Bottom (2.5P)	4.331	0.835	1.972	0.429	0.322	0.500	0.520	0.529
1605091110	9/16 - 12 UNC	H10	Bottom (1.5P)	4.331	0.835	1.972	0.429	0.322	0.500	0.520	0.529
1605096120	9/16 - 12 UNC	H10	Modified Bottom (2.5P)	4.331	0.835	1.972	0.429	0.322	0.500	0.520	0.529
1605091140	9/16 - 12 UNC	H10	Plug (4.5P)	4.331	0.835	1.972	0.429	0.322	0.500	0.520	0.529
1605096187	9/16 - 18 UNF	H7	Modified Bottom (2.5P)	3.937	0.835	1.972	0.429	0.322	0.500	0.534	0.540
1605091810	9/16 - 18 UNF	H10	Bottom (1.5P)	3.937	0.835	1.972	0.429	0.322	0.500	0.534	0.540
1605096180	9/16 - 18 UNF	H10	Modified Bottom (2.5P)	3.937	0.835	1.972	0.429	0.322	0.500	0.534	0.540
1605091840	9/16 - 18 UNF	H10	Plug (4.5P)	3.937	0.835	1.972	0.429	0.322	0.500	0.534	0.540
1605058117	5/8 - 11 UNC	H7	Modified Bottom (2.5P)	4.331	0.909	2.126	0.480	0.360	0.563	0.579	0.588
1605058150	5/8 - 11 UNC	H10	Bottom (1.5P)	4.331	0.909	2.126	0.480	0.360	0.563	0.579	0.588
1605058110	5/8 - 11 UNC	H10	Modified Bottom (2.5P)	4.331	0.909	2.126	0.480	0.360	0.563	0.579	0.588
1605058140	5/8 - 11 UNC	H10	Plug (4.5P)	4.331	0.909	2.126	0.480	0.360	0.563	0.579	0.588

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX





List 16050 (Continued)

EXOPRO[®] OIL-S-XPF, DIN Overall Length



FORMING HSS-Co V C/1.5P C/2.5P C/4.5P PACKED 1 PIECE

EDP Number	Thread Size	Thread Limit	Chamfer Type	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Tap Drill Size	
				L (Inch)	Lc (Inch)	L1 (Inch)	d (Inch)	k (Inch)	lk (Inch)	Min (Inch)	Max (Inch)
1605058187	5/8 - 18 UNF	H7	Modified Bottom (2.5P)	3.937	0.909	2.126	0.480	0.360	0.563	0.597	0.602
1605058810	5/8 - 18 UNF	H10	Bottom (1.5P)	3.937	0.909	2.126	0.480	0.360	0.563	0.597	0.602
1605058180	5/8 - 18 UNF	H10	Modified Bottom (2.5P)	3.937	0.909	2.126	0.480	0.360	0.563	0.597	0.602
1605058840	5/8 - 18 UNF	H10	Plug (4.5P)	3.937	0.909	2.126	0.480	0.360	0.563	0.597	0.602
1605034107	3/4 - 10 UNC	H7	Modified Bottom (2.5P)	4.921	1.000	2.433	0.590	0.442	0.688	0.699	0.709
1605034110	3/4 - 10 UNC	H10	Bottom (1.5P)	4.921	1.000	2.433	0.590	0.442	0.688	0.699	0.709
1605034100	3/4 - 10 UNC	H10	Modified Bottom (2.5P)	4.921	1.000	2.433	0.590	0.442	0.688	0.699	0.709
1605034140	3/4 - 10 UNC	H10	Plug (4.5P)	4.921	1.000	2.433	0.590	0.442	0.688	0.699	0.709
1605034167	3/4 - 16 UNF	H7	Modified Bottom (2.5P)	4.331	1.000	2.433	0.590	0.442	0.688	0.718	0.725
1605034610	3/4 - 16 UNF	H10	Bottom (1.5P)	4.331	1.000	2.433	0.590	0.442	0.688	0.718	0.725
1605034160	3/4 - 16 UNF	H10	Modified Bottom (2.5P)	4.331	1.000	2.433	0.590	0.442	0.688	0.718	0.725
1605034640	3/4 - 16 UNF	H10	Plug (4.5P)	4.331	1.000	2.433	0.590	0.442	0.688	0.718	0.725
1605078908	7/8 - 9 UNC	H8	Modified Bottom (2.5P)	5.512	1.110	2.654	0.697	0.523	0.750	0.818	0.830
1605078911	7/8 - 9 UNC	H11	Bottom (1.5P)	5.512	1.110	2.654	0.697	0.523	0.750	0.818	0.830
1605078901	7/8 - 9 UNC	H11	Modified Bottom (2.5P)	5.512	1.110	2.654	0.697	0.523	0.750	0.818	0.830
1605078941	7/8 - 9 UNC	H11	Plug (4.5P)	5.512	1.110	2.654	0.697	0.523	0.750	0.818	0.830
1605078148	7/8 - 14 UNF	H8	Modified Bottom (2.5P)	4.920	1.110	2.654	0.697	0.523	0.750	0.839	0.846
1605078149	7/8 - 14 UNF	H8	Plug (4.5P)	4.920	1.110	2.654	0.697	0.523	0.750	0.839	0.846
1605078111	7/8 - 14 UNF	H11	Bottom (1.5P)	4.920	1.110	2.654	0.697	0.523	0.750	0.839	0.846
1605078141	7/8 - 14 UNF	H11	Modified Bottom (2.5P)	4.920	1.110	2.654	0.697	0.523	0.750	0.839	0.846
1605078142	7/8 - 14 UNF	H11	Plug (4.5P)	4.920	1.110	2.654	0.697	0.523	0.750	0.839	0.846
1605001088	1 - 8 UNC	H8	Modified Bottom (2.5P)	6.300	1.252	3.012	0.800	0.600	0.813	0.936	0.949
1605018111	1 - 8 UNC	H11	Bottom (1.5P)	6.300	1.252	3.012	0.800	0.600	0.813	0.936	0.949
1605001081	1 - 8 UNC	H11	Modified Bottom (2.5P)	6.300	1.252	3.012	0.800	0.600	0.813	0.936	0.949
1605018411	1 - 8 UNC	H11	Plug (4.5P)	6.300	1.252	3.012	0.800	0.600	0.813	0.936	0.949
1605001128	1 - 12 UNF	H8	Modified Bottom (2.5P)	5.510	1.252	3.012	0.800	0.600	0.813	0.958	0.966
1605011211	1 - 12 UNF	H11	Bottom (1.5P)	5.510	1.252	3.012	0.800	0.600	0.813	0.958	0.966
1605001121	1 - 12 UNF	H11	Modified Bottom (2.5P)	5.510	1.252	3.012	0.800	0.600	0.813	0.958	0.966
1605011241	1 - 12 UNF	H11	Plug (4.5P)	5.510	1.252	3.012	0.800	0.600	0.813	0.958	0.966
1605011878	1- 1/8 - 7 UNC	H13	Modified Bottom (2.5P)	7.087	0.858	2.835	0.896	0.672	0.875	1.052	1.067
1605011888	1- 1/8 - 8 UN	H11	Modified Bottom (2.5P)	7.087	0.858	2.835	0.896	0.672	0.875	1.061	1.074
1605011826	1- 1/8 - 12 UNF	H11	Modified Bottom (2.5P)	5.906	0.835	2.362	0.896	0.672	0.875	1.083	1.091
1605012578	1- 1/4 - 7 UNC	H13	Modified Bottom (2.5P)	7.087	0.858	2.835	1.021	0.766	1.000	1.177	1.192
1605012588	1- 1/4 - 8 UN	H11	Modified Bottom (2.5P)	7.087	0.858	2.835	1.021	0.766	1.000	1.186	1.199
1605012526	1- 1/4 - 12 UNF	H11	Modified Bottom (2.5P)	5.906	0.835	2.362	1.021	0.766	1.000	1.208	1.216
1605013768	1- 3/8 - 6 UNC	H14	Modified Bottom (2.5P)	7.874	1.000	3.150	1.108	0.831	1.063	1.290	1.307
1605013788	1- 3/8 - 8 UN	H13	Modified Bottom (2.5P)	7.874	1.000	3.150	1.108	0.831	1.063	1.311	1.324
1605013126	1- 3/8 - 12 UNF	H11	Modified Bottom (2.5P)	6.693	0.835	2.677	1.108	0.831	1.063	1.333	1.341
1605011268	1- 1/2 - 6 UNC	H15	Modified Bottom (2.5P)	7.874	1.000	3.150	1.233	0.925	1.125	1.415	1.432
1605011288	1- 1/2 - 8 UN	H13	Modified Bottom (2.5P)	7.874	1.000	3.150	1.233	0.925	1.125	1.436	1.449
1605012126	1- 1/2 - 12 UNF	H11	Modified Bottom (2.5P)	6.693	0.835	2.677	1.233	0.925	1.125	1.458	1.466
1605016288	1- 5/8 - 8 UN	H13	Modified Bottom (2.5P)	7.874	1.000	3.150	1.305	0.979	1.125	1.561	1.574
1605017558	1- 3/4 - 5 UNC	H16	Modified Bottom (2.5P)	8.661	1.201	3.465	1.430	1.072	1.250	1.648	1.668
1605017588	1- 3/4 - 8 UN	H13	Modified Bottom (2.5P)	7.874	1.201	3.150	1.430	1.072	1.250	1.686	1.699

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel	300	400	17-4 PH		Aluminum		Nickel Alloy	Titanium				
Low	Medium	High							6061	Casting			Inconel	6Al4V	~35 HRC	35-45 HRC
1010	1035	1065	4140													
1018	1045		4340													
○	○	○	○	○	○*	○*	○*		○	○	○	○	○	○		
75-130SFM	75-130SFM	65-100SFM	65-100SFM	20-65SFM	20-50SFM	20-45SFM	15-40SFM		80-130SFM	75-110SFM	8-10SFM	8-10SFM	50-100SFM	8-20SFM		

*For Stainless Steel, please use non-water-soluble coolant or highly concentrated water-soluble coolant.

○ Good ○ Best

