




## List 16525

A BRAND A-LT-SFT, Long Shank

**A** SPIRAL FLUTE VC10 V C/2.5P 45° PACKED 1 PIECE



EDP Number	Thread Size	Thread Limit	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Number of Flutes	
			L (Inch)	Lc (Inch)	L1 (Inch)	d (Inch)	k (Inch)	lk (Inch)		
1652505608	●	No. 4 - 40 UNC	H2	3.150	0.197	0.750	0.141	0.110	0.188	2
1652505708	●	No. 4 - 48 UNF	H2	3.150	0.197	0.750	0.141	0.110	0.188	2
1652500308	●	No. 5 - 40 UNC	H2	3.937	0.201	0.760	0.141	0.110	0.188	2
1652505908	●	No. 5 - 44 UNF	H2	3.937	0.201	0.760	0.141	0.110	0.188	2
1652500608	●	No. 6 - 32 UNC	H3	4.724	0.248	0.783	0.141	0.110	0.188	2
1652500708	●	No. 6 - 40 UNF	H2	3.937	0.248	0.783	0.141	0.110	0.188	2
1652500908	●	No. 8 - 32 UNC	H3	4.724	0.252	0.827	0.168	0.131	0.250	2
1652501008	●	No. 8 - 36 UNF	H2	3.937	0.252	0.827	0.168	0.131	0.250	2
1652501108	●	No. 10 - 24 UNC	H3	4.921	0.327	0.976	0.194	0.152	0.250	2
1652501308	●	No. 10 - 32 UNF	H3	5.906	0.327	0.976	0.194	0.152	0.250	2
1652501408	●	No. 12 - 24 UNC	H3	4.921	0.331	1.177	0.220	0.165	0.281	2
1652501508	●	No. 12 - 28 UNF	H3	4.921	0.331	1.177	0.220	0.165	0.281	2
1652501708	●	1/4 - 20 UNC	H5	5.906	0.398	1.177	0.255	0.191	0.313	2
1652501908	●	1/4 - 28 UNF	H4	5.906	0.398	1.177	0.255	0.191	0.313	2
1652502108	●	5/16 - 18 UNC	H5	5.906	0.445	1.378	0.318	0.238	0.375	3
1652502308	●	5/16 - 24 UNF	H4	5.906	0.445	1.378	0.318	0.238	0.375	3
1652502508	●	3/8 - 16 UNC	H5	5.906	0.500	1.535	0.381	0.286	0.438	3
1652502708	●	3/8 - 24 UNF	H4	5.906	0.500	1.378	0.381	0.286	0.438	3
1652502908	●	7/16 - 14 UNC	H5	5.906	0.571	2.362	0.323	0.242	0.406	3
1652503108	●	7/16 - 20 UNF	H5	5.906	0.571	2.362	0.323	0.242	0.406	3
1652503308	●	1/2 - 13 UNC	H5	7.087	0.614	2.835	0.367	0.275	0.438	3
1652503508	●	1/2 - 20 UNF	H5	7.087	0.614	2.835	0.367	0.275	0.438	3
1652503708	●	9/16 - 12 UNC	H5	7.087	0.665	2.835	0.429	0.322	0.500	3
1652503908	●	9/16 - 18 UNF	H5	7.087	0.665	2.835	0.429	0.322	0.500	3
1652504108	●	5/8 - 11 UNC	H5	7.087	0.728	2.835	0.480	0.360	0.563	3
1652504308	●	5/8 - 18 UNF	H5	7.087	0.728	2.835	0.480	0.360	0.563	3
1652504508	●	3/4 - 10 UNC	H5	7.874	1.000	3.150	0.590	0.442	0.688	4
1652504708	●	3/4 - 16 UNF	H5	7.874	1.000	3.150	0.590	0.442	0.688	4
1652504908	●	7/8 - 9 UNC	H6	7.874	1.110	3.150	0.697	0.523	0.750	4
1652505108	●	7/8 - 14 UNF	H6	7.874	1.110	3.150	0.697	0.523	0.750	4
1652505308	●	1 - 8 UNC	H6	7.874	1.252	3.465	0.800	0.600	0.813	4
1652505508	●	1 - 12 UNF	H6	7.874	1.252	3.465	0.800	0.600	0.813	4

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel	300	400	17-4 PH		Aluminum		Nickel Alloy	Titanium				
Low	Medium	High							6061	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
1010	1035	1065	4140	4340				7075								
○	○	○	○	○	○	○	○	○	○			○				
80-120 SFM	80-120 SFM	80-120 SFM	35-50 SFM	20-40 SFM	15-35 SFM	15-35 SFM	15-25 SFM	50-80 SFM	70-120 SFM	70-120 SFM			30-55 SFM			

○ Good ○ Best

