



List 16535

A BRAND A-LT-POT, Long Shank

A **VC10** **PACKED 1 PIECE**



EDP	Thread Size	Thread Limit	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Number of Flutes	
			L (Inch)	Lc (Inch)	L1 (Inch)	d (Inch)	k (Inch)	lk (Inch)		
1653506008	●	No. 4 - 40 UNC	H2	3.149	0.342	0.751	0.141	0.110	0.188	2
1653506108	●	No. 4 - 48 UNF	H2	3.149	0.342	0.751	0.141	0.110	0.188	2
1653500708	●	No. 5 - 40 UNC	H2	3.937	0.350	0.759	0.141	0.110	0.188	3
1653506308	●	No. 5 - 44 UNF	H2	3.937	0.350	0.759	0.141	0.110	0.188	3
1653501008	●	No. 6 - 32 UNC	H3	4.724	0.429	0.842	0.141	0.110	0.188	3
1653501108	●	No. 6 - 40 UNF	H2	3.937	0.433	0.846	0.141	0.110	0.188	3
1653501308	●	No. 8 - 32 UNC	H3	4.724	0.444	0.897	0.168	0.131	0.250	3
1653501408	●	No. 8 - 36 UNF	H2	3.937	0.444	0.897	0.168	0.131	0.250	3
1653501508	●	No. 10 - 24 UNC	H3	4.921	0.574	1.059	0.194	0.152	0.250	3
1653501708	●	No. 10 - 32 UNF	H3	5.906	0.582	1.066	0.194	0.152	0.250	3
1653501808	●	No. 12 - 24 UNC	H3	4.921	0.590	1.271	0.220	0.165	0.280	3
1653501908	●	No. 12 - 28 UNF	H3	4.921	0.590	1.271	0.220	0.165	0.280	3
1653502108	●	1/4 - 20 UNC	H5	5.906	0.704	1.366	0.255	0.191	0.287	3
1653502308	●	1/4 - 28 UNF	H4	5.906	0.704	1.366	0.255	0.191	0.287	3
1653502508	●	5/16 - 18 UNC	H5	5.906	0.803	1.633	0.318	0.238	0.343	3
1653502708	●	5/16 - 24 UNF	H4	5.906	0.803	1.633	0.318	0.238	0.343	3
1653502908	●	3/8 - 16 UNC	H5	5.906	0.917	1.897	0.381	0.286	0.398	3
1653503108	●	3/8 - 24 UNF	H4	5.906	0.929	1.897	0.381	0.286	0.398	3
1653503308	●	7/16 - 14 UNC	H5	5.906	0.858	2.362	0.323	0.242	0.406	3
1653503508	●	7/16 - 20 UNF	H5	5.906	0.858	2.362	0.323	0.242	0.406	3
1653503708	●	1/2 - 13 UNC	H5	7.087	0.921	2.834	0.367	0.275	0.438	3
1653503908	●	1/2 - 20 UNF	H5	7.087	0.921	2.834	0.367	0.275	0.438	3
1653504108	●	9/16 - 12 UNC	H5	7.087	1.000	2.834	0.429	0.322	0.500	3
1653504308	●	9/16 - 18 UNF	H5	7.087	1.000	2.834	0.429	0.322	0.500	3
1653504508	●	5/8 - 11 UNC	H5	7.087	1.090	2.834	0.480	0.360	0.563	3
1653504708	●	5/8 - 18 UNF	H5	7.087	1.090	2.834	0.480	0.360	0.563	3
1653504908	●	3/4 - 10 UNC	H5	7.874	1.200	3.149	0.590	0.442	0.688	3
1653505108	●	3/4 - 16 UNF	H5	7.874	1.200	3.149	0.590	0.442	0.688	3
1653505308	●	7/8 - 9 UNC	H6	7.874	1.334	3.149	0.697	0.523	0.750	3
1653505508	●	7/8 - 14 UNF	H6	7.874	1.334	3.149	0.697	0.523	0.750	3
1653505708	●	1 - 8 UNC	H6	7.874	1.500	3.149	0.800	0.600	0.813	3
1653505908	●	1 - 12 UNF	H6	7.874	1.500	3.149	0.800	0.600	0.813	3

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium				
Low	Medium	High			300	400	17-4 PH		6061 7075	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
1010	1035	1065	4140	4340	300	400	17-4 PH	6061 7075	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC	
○	○	○	○	○	○	○	○	○	○			○				
80-120 SFM	80-120 SFM	80-120 SFM	40-65 SFM	35-55 SFM	25-75 SFM	25-60 SFM	25-60 SFM	60-100 SFM	70-120 SFM	70-120 SFM		40-65 SFM				

○ Good ○ Best



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX