



List 16555

A BRAND A-OIL-POT, DIN Overall Length



SPIRAL POINT	VC10	V	3 FLUTE	C/4P	0°	PACKED 1 PIECE
--------------	------	---	---------	------	----	-------------------



EDP	Thread Size	Thread Limit	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Number of Flutes
			L (Inch)	Lc (Inch)	L1 (Inch)	d (Inch)	k (Inch)	lk (Inch)	
1655500108	1/4 - 20 UNC	H5	3.150	0.598	1.181	0.255	0.191	0.313	3
1655500208	1/4 - 28 UNF	H4	3.150	0.598	1.181	0.255	0.191	0.313	3
1655500308	5/16 - 18 UNC	H5	3.543	0.665	1.377	0.318	0.238	0.375	3
1655500408	5/16 - 24 UNF	H4	3.543	0.665	1.377	0.318	0.238	0.375	3
1655500508	3/8 - 16 UNC	H5	3.937	0.751	1.535	0.381	0.286	0.438	3
1655500608	3/8 - 24 UNF	H4	3.543	0.751	1.377	0.381	0.286	0.438	3
1655500708	7/16 - 14 UNC	H5	3.937	0.858	1.291	0.323	0.242	0.406	3
1655500808	7/16 - 20 UNF	H5	3.937	0.858	1.291	0.323	0.242	0.406	3
1655500908	1/2 - 13 UNC	H5	4.331	0.921	1.354	0.367	0.275	0.438	3
1655501008	1/2 - 20 UNF	H5	3.937	0.921	1.354	0.367	0.275	0.438	3
1655501108	9/16 - 12 UNC	H5	4.331	1.000	1.472	0.429	0.322	0.500	3
1655501208	9/16 - 18 UNF	H5	3.937	1.000	1.472	0.429	0.322	0.500	3
1655501308	5/8 - 11 UNC	H5	4.331	1.090	1.562	0.480	0.360	0.563	3
1655501408	5/8 - 18 UNF	H5	3.937	1.090	1.562	0.480	0.360	0.563	3
1655501508	3/4 - 10 UNC	H5	4.921	1.200	1.712	0.590	0.442	0.688	3
1655501608	3/4 - 16 UNF	H5	4.331	1.200	1.712	0.590	0.442	0.688	3
1655501708	7/8 - 9 UNC	H6	5.512	1.334	1.885	0.697	0.523	0.750	3
1655501808	7/8 - 14 UNF	H6	4.921	1.334	1.885	0.697	0.523	0.750	3
1655501908	1 - 8 UNC	H6	6.299	1.500	2.090	0.800	0.600	0.813	3
1655502008	1 - 12 UNF	H6	5.512	1.500	2.090	0.800	0.600	0.813	3

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium				
Low	Medium	High			300	400	17-4 PH		6061 7075	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
1010	1035	1065	4140	4340	300	400	17-4 PH	6061 7075	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC	
○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
100-200 SFM	100-200 SFM	100-200 SFM	50-120 SFM	45-110 SFM	40-120 SFM	40-120 SFM	40-100 SFM	80-160 SFM	90-220 SFM	90-220 SFM		60-120 SFM				

○ Good ○ Best

