




List 2010

EXOCARB® AERO BLIZZARD

SPEED FEED 1491	CARBIDE	BR	2 FLUTE	30°		SHANK h6	REG	PACKED 1 PIECE
---------------------------	----------------	-----------	----------------	------------	--	--------------------	------------	--------------------------

Radius Tolerance	
1/8" ≤ D ≤ 1"	+0 / -0.002"



EDP Number		Diameter	Length of Cut	Overall Length	Shank Diameter
		D (Fractional Size)	Lc (Inch)	L (Inch)	d (Inch)
20100100	●	1/8	0.375	1.500	0.125
20100200	●	3/16	0.563	2.000	0.188
20100300	●	1/4	0.750	2.500	0.250
20100400	●	5/16	0.813	2.500	0.313
20100500	●	3/8	1.000	2.500	0.375
20100600	●	7/16	1.000	2.750	0.438
20100700	●	1/2	1.250	3.000	0.500
20100800	●	5/8	1.625	3.500	0.625
20100900	●	3/4	1.625	4.000	0.750
20101000	●	1	2.000	5.000	1.000

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

P					M			K	N		S	H						
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel					
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium						
Low	Medium	High			300	400	17-4 PH		6061	Casting			Inconel	6Al4V	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
1010	1035	1045	1065	4140	4340													
1018	1045	1065	4140	4340														

○ Good ⊙ Best

