



# EXOPRO® AERO-HBC 60

Diamond Coated Routers for Milling CFRP and Other Composites

ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

## List 2068

EXOPRO® AERO-HBC 60, 60° Compression Router

<b>SPEED FEED</b> 1507	<b>CARBIDE</b>	<b>DIA</b>	<b>2 FLUTE</b>	<b>60°</b>		<b>SHANK</b> h6	<b>REG</b>	<b>LONG</b>	<b>EXTRA LONG</b>	<b>PACKED</b> 1 PIECE
---------------------------	----------------	------------	----------------	------------	--	--------------------	------------	-------------	-------------------	--------------------------

Cutting Diameter Tolerance	
1/4" ≤ D ≤ 1/2"	+0 / -0.002"



EDP Number		Diameter	Compression Length	Length of Cut	Overall Length	Shank Diameter
		D (Fractional Size)	L2 (Inch)	Lc (Inch)	L (Inch)	d (Inch)
20682516	●	1/4	0.188	0.750	3.000	0.250
20683516	●	3/8	0.281	0.750	3.000	0.375
20683616	●	3/8	0.281	2.000	4.000	0.375
20685016	●	1/2	0.375	1.000	3.000	0.500
20685116	●	1/2	0.375	2.000	4.000	0.500

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



Carbon Fiber (CFRP)	Glass Fiber (GFRP)	Aramid Fiber (AFRP)	Honeycomb					Carbon/ Carbon	Carbon Fiber/ Aluminum Stack	Carbon Fiber/ Titanium Stack	Carbon Fiber/Al/ Ti/CRES Stack
			CFRP/ Nomex	GFRP/ Nomex	AFRP	CFRP/Al	Al/Al				
◎	◎	○	◎	◎	◎	◎	◎				

○ Good ◎ Best

