



List 2106

EXOCARB® AERO UVX-TI-CR-5FL

SPEED FEED 1374	CARBIDE	EXO®	5 FLUTE	41-43°		SHANK h6	STUB	REG	LONG	PACKED 1 PIECE
---------------------------	----------------	-------------	----------------	---------------	--	--------------------	-------------	------------	-------------	--------------------------

Cutting Diameter Tolerance	
1/2" ≤ D ≤ 1-1/4"	+0 / -0.002"



EDP Number	Dia.	Corner Radius		Length of Cut		Overall Length		Shank Dia.	
		D (Fractional Size)	R (Inch)	Lc (Inch)	L (Inch)	d (Inch)			
21062111	●	1/2	0.030	0.625	2.500	0.500			
21062211	●	1/2	0.060	0.625	2.500	0.500			
21062311	●	1/2	0.090	0.625	2.500	0.500			
21062411	●	1/2	0.120	0.625	2.500	0.500			
21062511	●	1/2	0.030	1.000	3.000	0.500			
21062611	●	1/2	0.060	1.000	3.000	0.500			
21062711	●	1/2	0.090	1.000	3.000	0.500			
21062811	●	1/2	0.120	1.000	3.000	0.500			
21062911	●	1/2	0.015	1.250	3.500	0.500			
21063011	●	1/2	0.030	1.250	3.500	0.500			
21063111	●	1/2	0.060	1.250	3.500	0.500			
21063211	●	1/2	0.090	1.250	3.500	0.500			
21063311	●	1/2	0.120	1.250	3.500	0.500			
21063411	●	1/2	0.015	1.625	3.500	0.500			
21063511	●	1/2	0.030	1.625	3.500	0.500			
21063611	●	1/2	0.060	1.625	3.500	0.500			
21063711	●	1/2	0.090	1.625	3.500	0.500			
21063811	●	1/2	0.120	1.625	3.500	0.500			
21063911	●	5/8	0.030	1.250	3.500	0.625			
21064011	●	5/8	0.060	1.250	3.500	0.625			
21064111	●	5/8	0.090	1.250	3.500	0.625			
21064211	●	5/8	0.120	1.250	3.500	0.625			
21064311	●	5/8	0.030	1.875	4.000	0.625			
21064411	●	5/8	0.060	1.875	4.000	0.625			
21064511	●	5/8	0.090	1.875	4.000	0.625			
21064611	●	5/8	0.120	1.875	4.000	0.625			
21064711	●	3/4	0.030	1.500	4.000	0.750			
21064811	●	3/4	0.060	1.500	4.000	0.750			
21064911	●	3/4	0.090	1.500	4.000	0.750			
21065011	●	3/4	0.120	1.500	4.000	0.750			
21065111	●	3/4	0.150	1.500	4.000	0.750			

● Stocked ○ Available Upon Request; MOQ May Apply
▲ Globally Stocked



EDP Number	Dia.	Corner Radius		Length of Cut		Overall Length		Shank Dia.	
		D (Fractional Size)	R (Inch)	Lc (Inch)	L (Inch)	d (Inch)			
21065211	●	3/4	0.030	2.250	5.000	0.750			
21065311	●	3/4	0.060	2.250	5.000	0.750			
21065411	●	3/4	0.090	2.250	5.000	0.750			
21065511	●	3/4	0.120	2.250	5.000	0.750			
21065611	●	3/4	0.150	2.250	5.000	0.750			
21065711	●	1	0.030	1.500	4.000	1.000			
21065811	●	1	0.060	1.500	4.000	1.000			
21065911	●	1	0.090	1.500	4.000	1.000			
21066011	●	1	0.120	1.500	4.000	1.000			
21066111	●	1	0.150	1.500	4.000	1.000			
21066211	●	1	0.030	3.000	6.000	1.000			
21066311	●	1	0.060	3.000	6.000	1.000			
21066411	●	1	0.090	3.000	6.000	1.000			
21066511	●	1	0.120	3.000	6.000	1.000			
21066611	●	1	0.150	3.000	6.000	1.000			
21066711	●	1-1/4	0.030	1.500	4.000	1.250			
21066811	●	1-1/4	0.060	1.500	4.000	1.250			
21066911	●	1-1/4	0.090	1.500	4.000	1.250			
21067011	●	1-1/4	0.120	1.500	4.000	1.250			
21067111	●	1-1/4	0.150	1.500	4.000	1.250			
21067211	●	1-1/4	0.030	3.000	6.000	1.250			
21067311	●	1-1/4	0.060	3.000	6.000	1.250			
21067411	●	1-1/4	0.090	3.000	6.000	1.250			
21067511	●	1-1/4	0.120	3.000	6.000	1.250			
21067611	●	1-1/4	0.150	3.000	6.000	1.250			
21067711	●	1-1/4	0.030	4.000	7.000	1.250			
21067811	●	1-1/4	0.060	4.000	7.000	1.250			
21067911	●	1-1/4	0.090	4.000	7.000	1.250			
21068011	●	1-1/4	0.120	4.000	7.000	1.250			
21068111	●	1-1/4	0.150	4.000	7.000	1.250			

● Stocked ○ Available Upon Request; MOQ May Apply
▲ Globally Stocked



P					M			K	N		S		H				
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel				
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium					
Low	Medium	High			300	400	17-4 PH		6061	7075			Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
1010	1035	1045	1065	4140	4340												
1018	1045	1065															

○ Good ⊗ Best

