




List 230

HY-PRO® DIN OIL-TIN-SFT, DIN Overall Length

SPIRAL FLUTE	HSSE	TIN	C/2.5P	45°	PACKED 1 PIECE
--------------	------	-----	--------	-----	----------------



EDP Number	Thread Size	Overall Length		Thread Length		Neck Length		Shank Diameter		Square Width		Square Length		Number of Flutes
		L (Inch)	Lc (Inch)	L1 (Inch)	d (Inch)	k (Inch)	lk (Inch)							
2330005	1/4 - 20 UNC	3.150	0.402	1.181	0.255	0.191	0.313	3						
2330405	1/4 - 28 UNF	3.150	0.402	1.181	0.255	0.191	0.313	3						
2330805	5/16 - 18 UNC	3.543	0.445	1.378	0.318	0.238	0.375	3						
2331205	5/16 - 24 UNF	3.543	0.445	1.378	0.318	0.238	0.375	3						
2331605	3/8 - 16 UNC	3.937	0.500	1.378	0.381	0.286	0.438	3						
2331805	3/8 - 24 UNF	3.937	0.500	1.378	0.381	0.286	0.438	3						
2332005	7/16 - 14 UNC	3.937	0.571	1.713	0.323	0.242	0.406	3						
2332205	7/16 - 20 UNF	3.937	0.571	1.713	0.323	0.242	0.406	3						
2332405	1/2 - 13 UNC	4.331	0.614	1.934	0.367	0.275	0.438	3						
2332605	1/2 - 20 UNF	3.937	0.614	1.934	0.367	0.275	0.438	3						
2333005	9/16 - 18 UNF	3.937	0.665	1.972	0.429	0.322	0.500	4						
2333205	5/8 - 11 UNC	4.331	0.728	2.126	0.480	0.360	0.563	4						
2333405	5/8 - 18 UNF	3.937	0.728	2.126	0.480	0.360	0.563	4						
2333605	3/4 - 10 UNC	4.921	0.799	2.434	0.590	0.442	0.688	4						
2333805	3/4 - 16 UNF	4.331	0.799	2.434	0.590	0.442	0.688	4						
2334005	7/8 - 9 UNC	5.512	0.890	2.654	0.697	0.523	0.750	4						
2334205	7/8 - 14 UNF	4.921	0.890	2.654	0.697	0.523	0.750	4						
2334405	1 - 8 UNC	6.299	1.000	3.118	0.800	0.600	0.813	4						

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel	Aluminum		Nickel Alloy		Titanium	Hardened Steel						
Low	Medium	High			300	400				17-4 PH	6061 7075	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
1010	1035	1065	4140	4340	300	400	17-4 PH	6061 7075	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC	
○	○	⊗	⊗	⊗	○	○	○	○	○			○				
50-120 SFM	45-110 SFM	40-100 SFM	45-110 SFM	20-60 SFM	20-70 SFM	30-50 SFM	20-50 SFM	40-100 SFM	50-125 SFM	50-110 SFM		20-60 SFM				

○ Good ⊗ Best

