




List 241

HY-PRO® DC EX-DC-HT

STRAIGHT FLUTE	HSSE	N	C/1.5P	C/4P	0°	PACKED 1 PIECE
----------------	------	---	--------	------	----	-------------------



EDP	Thread Size	Thread Limit	Chamfer Type	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Number of Flutes	
				L (mm)	Lc (mm)	L1 (mm)	d (mm)	k (mm)	lk (mm)		
2410203	●	M3 x 0.5	D3	Bottom (1.5P)	49.20	7.30	17.20	3.58	2.79	4.76	3
2494903	●	M3 x 0.5	D3	Plug (4P)	49.20	7.30	17.20	3.58	2.79	4.76	3
2495003	●	M4 x 0.7	D4	Bottom (1.5P)	54.00	10.10	20.80	4.27	3.33	6.35	3
2410303	●	M4 x 0.7	D4	Plug (4P)	54.00	10.10	20.80	4.27	3.33	6.35	3
2410603	●	M5 x 0.8	D5	Bottom (1.5P)	60.30	11.80	24.40	4.93	3.86	6.35	3
2495103	●	M5 x 0.8	D5	Plug (4P)	60.30	11.80	24.40	4.93	3.86	6.35	3
2410803	●	M6 x 1	D5	Bottom (1.5P)	63.50	14.60	28.00	6.48	4.85	7.94	3
2495203	●	M6 x 1	D5	Plug (4P)	63.50	14.60	28.00	6.48	4.85	7.94	3
2411203	●	M8 x 1.25	D5	Bottom (1.5P)	69.10	15.00	28.60	8.08	6.05	9.53	4
2411103	●	M8 x 1.25	D5	Plug (4P)	69.10	15.00	28.60	8.08	6.05	9.53	4
2411603	●	M10 x 1.25	D5	Bottom (1.5P)	74.60	18.00	31.80	9.68	7.26	11.11	4
2495303	●	M10 x 1.25	D5	Plug (4P)	74.60	18.00	31.80	9.68	7.26	11.11	4
2495403	●	M10 x 1.5	D6	Bottom (1.5P)	74.60	18.00	31.80	9.68	7.26	11.11	4
2411703	●	M10 x 1.5	D6	Plug (4P)	74.60	18.00	31.80	9.68	7.26	11.11	4
2495503	●	M12 x 1.75	D6	Bottom (1.5P)	85.70	21.00	49.10	9.32	6.99	11.11	4
2412103	●	M12 x 1.75	D6	Plug (4P)	85.70	21.00	49.10	9.32	6.99	11.11	4

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S	H					
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel				
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium					
Low	Medium	High			300	400	17-4 PH	6061 7075	Casting	Inconel			6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
1010	1035	1065	4140	4340				○	○	○							
1018	1045							○	○	○							
								○	○	○							
								○	○	○							

○ Good ○ Best

