




List 250

HY-PRO® DIN-POT, DIN Overall Length

SPIRAL POINT	HSSE	S/O	C/4P	0°	PACKED 1 PIECE
--------------	------	-----	------	----	-------------------



EDP	●	Thread Size	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Number of Flutes
			L (Inch)	Lc (Inch)	L1 (Inch)	d (Inch)	k (Inch)	lk (Inch)	
2511401	●	No. 4 - 40 UNC	2.205	0.295	0.705	0.141	0.110	0.188	2
2512401	●	No. 6 - 32 UNC	2.205	0.370	0.783	0.141	0.110	0.188	2
2517801	●	No. 8 - 32 UNC	2.480	0.374	0.827	0.168	0.131	0.250	3
2513401	●	No. 10 - 24 UNC	2.756	0.492	0.976	0.194	0.152	0.250	3
2518801	●	No. 10 - 32 UNF	2.756	0.492	0.984	0.194	0.152	0.250	3
2530001	●	1/4 - 20 UNC	3.150	0.594	1.177	0.255	0.191	0.313	3
2530401	●	1/4 - 28 UNF	3.150	0.594	1.189	0.255	0.191	0.313	3
2530801	●	5/16 - 18 UNC	3.543	0.665	1.378	0.318	0.238	0.375	3
2531201	●	5/16 - 24 UNF	3.543	0.657	1.378	0.318	0.238	0.375	3
2531601	●	3/8 - 16 UNC	3.937	0.752	1.378	0.381	0.286	0.438	3
2531801	●	3/8 - 24 UNF	3.937	0.740	1.378	0.381	0.286	0.438	3
2532001	●	7/16 - 14 UNC	3.937	0.858	1.291	0.323	0.242	0.406	3
2532201	●	7/16 - 20 UNF	3.937	0.858	1.291	0.323	0.242	0.406	3
2532401	●	1/2 - 13 UNC	4.331	0.921	1.354	0.367	0.275	0.438	3
2532601	●	1/2 - 20 UNF	3.937	0.921	1.354	0.367	0.275	0.438	3
2533201	●	5/8 - 11 UNC	4.331	1.091	1.563	0.480	0.360	0.563	3
2533401	●	5/8 - 18 UNF	3.937	1.091	1.563	0.480	0.360	0.563	3
2533601	●	3/4 - 10 UNC	4.921	1.201	1.713	0.590	0.442	0.688	3
2533801	●	3/4 - 16 UNF	4.331	1.201	1.713	0.590	0.442	0.688	3

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium				
Low	Medium	High			300	400	17-4 PH		6061 7075	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
○	○	⊗	⊗	○	○	○	○	○					○			
25-80 SFM	20-50 SFM	20-45 SFM	20-50 SFM	15-30 SFM	20-45 SFM	20-40 SFM	15-20 SFM	25-75 SFM					15-35 SFM			

○ Good ⊗ Best

