




List 259

HY-PRO® DIN-POT, DIN Overall Length

SPIRAL POINT	HSSE	S/O	3 FLUTE	C/4P	0°	PACKED 1 PIECE
--------------	------	-----	---------	------	----	-------------------



EDP	Thread Size	Class of Fit	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	
			L (mm)	Lc (mm)	L1 (mm)	d (mm)	k (mm)	lk (mm)	
2590401	●	M3 x 0.5	6H	56.00	6.00	18.00	3.58	2.79	4.76
2590601	●	M4 x 0.7	6H	63.00	8.40	21.00	4.27	3.33	6.35
2590801	●	M5 x 0.8	6H	70.00	9.60	25.00	4.93	3.86	6.35
2591001	●	M6 x 1	6H	80.00	12.00	30.00	6.48	4.85	7.94
2591401	●	M8 x 1.25	6H	90.00	15.00	35.00	8.08	6.05	9.53
2591701	●	M10 x 1.25	6H	100.00	18.00	39.00	9.68	7.26	11.11
2591801	●	M10 x 1.5	6H	100.00	18.00	39.00	9.68	7.26	11.11
2592101	●	M12 x 1.25	6H	100.00	21.00	32.00	9.32	6.99	11.11
2592201	●	M12 x 1.5	6H	100.00	21.00	32.00	9.32	6.99	11.11
2592301	●	M12 x 1.75	6H	110.00	21.00	32.00	9.32	6.99	11.11
2592501	●	M14 x 1.5	6H	100.00	24.00	36.00	10.90	8.18	12.70
2592601	●	M14 x 2	6H	110.00	24.00	36.00	10.90	8.18	12.70
2592801	●	M16 x 1.5	6H	100.00	24.00	36.00	12.19	9.14	14.29
2592901	●	M16 x 2	6H	110.00	24.00	36.00	12.19	9.14	14.29
2593001	●	M18 x 1.5	6H	110.00	30.00	43.00	13.77	10.31	15.88
2593201	●	M18 x 2.5	6H	125.00	30.00	43.00	13.77	10.31	15.88
2593401	●	M20 x 1.5	6H	125.00	30.00	44.00	16.56	12.42	17.46
2593601	●	M20 x 2.5	6H	140.00	30.00	44.00	16.56	12.42	17.46

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S	H				
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium				
Low	Medium	High			300	400	17-4 PH		6061	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
1010	1018	1035	1045	1065	4140	4340										
○	○	⊗	⊗	○	○	○	○	○					○			
25-80 SFM	20-50 SFM	20-45 SFM	20-50 SFM	15-30 SFM	20-45 SFM	20-40 SFM	15-20 SFM	25-75 SFM					15-35 SFM			

○ Good ⊗ Best

