



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

## List 2650

EXOPRO® AERO-MFR, Finishing Router

<b>SPEED FEED</b> 1509	<b>CARBIDE</b>	<b>DIA</b>	<b>15°</b>	<b>SHANK</b> h6	<b>REG</b>	<b>LONG</b>	<b>PACKED</b> 1 PIECE
---------------------------	----------------	------------	------------	--------------------	------------	-------------	--------------------------

Cutting Diameter Tolerance	
1/4" ≤ D ≤ 1/2"	+0 / -0.002"



EDP Number		Diameter		Length of Cut		Overall Length		Shank Diameter		Number of Flutes
		D (Fractional Size)		Lc (Inch)		L (Inch)		d (Inch)		
26500316	●	1/4		0.750		2.500		0.250		8
26501316	●	1/4		1.000		3.000		0.250		8
26500616	●	3/8		1.125		3.000		0.375		12
26501516	●	3/8		1.500		3.000		0.375		12
26500716	●	1/2		1.500		4.000		0.500		14
26501716	●	1/2		2.000		4.000		0.500		14

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



Carbon Fiber (CFRP)	Glass Fiber (GFRP)	Aramid Fiber (AFRP)	Honeycomb					Carbon/Carbon	Carbon Fiber/Aluminum Stack	Carbon Fiber/Titanium Stack	Carbon Fiber/Al/Ti/CRES Stack
			CFRP/Nomex	GFRP/Nomex	AFRP	CFRP/Al	Al/Al				
◎	◎		○	○		○	○	◎			

○ Good ◎ Best

