




List 288

HY-PRO® SEVEN POT

SPIRAL POINT	HSS	BR	S/O	TiN	2 FLUTE	C/SP	0°	PACKED 1 PIECE
--------------	-----	----	-----	-----	---------	------	----	-------------------



EDP	Thread Size	Class of Fit	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Surface Treatment	
			L (mm)	Lc (mm)	L1 (mm)	d (mm)	k (mm)	lk (mm)		
2888000	●	M3 x 0.5	6H	49.20	8.30	15.80	3.58	2.79	4.76	Bright
2888001	●	M3 x 0.5	6H	49.20	8.30	15.80	3.58	2.79	4.76	Steam Oxide
2888005	●	M3 x 0.5	6H	49.20	8.30	15.80	3.58	2.79	4.76	TiN
2888100	●	M4 x 0.7	6H	54.00	10.00	19.30	4.27	3.33	6.35	Bright
2888101	●	M4 x 0.7	6H	54.00	10.00	19.30	4.27	3.33	6.35	Steam Oxide
2888105	●	M4 x 0.7	6H	54.00	10.00	19.30	4.27	3.33	6.35	TiN
2888200	●	M5 x 0.8	6H	60.30	13.00	22.40	4.93	3.86	6.35	Bright
2888201	●	M5 x 0.8	6H	60.30	13.00	22.40	4.93	3.86	6.35	Steam Oxide
2888205	●	M5 x 0.8	6H	60.30	13.00	22.40	4.93	3.86	6.35	TiN
2888300	●	M6 x 1	6H	63.50	16.50	25.90	6.48	4.85	7.94	Bright
2888301	●	M6 x 1	6H	63.50	16.50	25.90	6.48	4.85	7.94	Steam Oxide
2888305	●	M6 x 1	6H	63.50	16.50	25.90	6.48	4.85	7.94	TiN
2888400	●	M8 x 1.25	6H	69.10	18.00	28.80	8.08	6.05	9.53	Bright
2888401	●	M8 x 1.25	6H	69.10	18.00	28.80	8.08	6.05	9.53	Steam Oxide
2888405	●	M8 x 1.25	6H	69.10	18.00	28.80	8.08	6.05	9.53	TiN
2888500	●	M10 x 1.5	6H	74.60	20.10	32.50	9.68	7.26	11.11	Bright
2888501	●	M10 x 1.5	6H	74.60	20.10	32.50	9.68	7.26	11.11	Steam Oxide
2888505	●	M10 x 1.5	6H	74.60	20.10	32.50	9.68	7.26	11.11	TiN
2888600	●	M12 x 1.75	6H	85.70	23.90	34.90	9.32	6.99	11.11	Bright
2888601	●	M12 x 1.75	6H	85.70	23.90	34.90	9.32	6.99	11.11	Steam Oxide
2888605	●	M12 x 1.75	6H	85.70	23.90	34.90	9.32	6.99	11.11	TiN

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked
 Note: Other coatings are available upon request.



P					M			K	N		S		H				
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel				
Carbon Steel			Alloy Steel	Die Steel	Aluminum		Nickel Alloy		Titanium								
Low	Medium	High			6061	Casting				Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC		
1010	1035	1045	1065	4140	4340	300	400	17-4 PH	6061	7075	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
○	○								○	○							
50-90 SFM	40-80 SFM								30-80 SFM	30-80 SFM							

○ Good ○ Best



ABOUT OSG
DRILLING
THREADING
MILLING
HOLDERS
INDEX