




# List 308

EXOPIPE, NPT

SPIRAL FLUTE	HSSE	S/O	TiN	15°	PACKED 1 PIECE
--------------	------	-----	-----	-----	-------------------



EDP	Thread Size	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Number of Flutes	Surface Treatment	
		L (Inch)	Lc (Inch)	L1 (Inch)	d (Inch)	k (Inch)	lk (Inch)			
1735001	●	1/16 - 27 NPT	2.126	0.689	0.925	0.313	0.234	0.375	4	Steam Oxide
1735005	●	1/16 - 27 NPT	2.126	0.689	0.925	0.313	0.234	0.375	4	TiN
1735101	●	1/8 - 27 NPT	2.126	0.752	0.988	0.438	0.328	0.375	4	Steam Oxide
1735201	●	1/8 - 27 NPT	2.126	0.752	-	0.313	0.234	0.375	4	Steam Oxide
1735105	●	1/8 - 27 NPT	2.126	0.752	0.988	0.438	0.328	0.375	4	TiN
1735205	●	1/8 - 27 NPT	2.126	0.752	-	0.313	0.234	0.375	4	TiN
1735301	●	1/4 - 18 NPT	2.437	1.091	1.346	0.563	0.421	0.438	4	Steam Oxide
1735305	●	1/4 - 18 NPT	2.437	1.091	1.346	0.563	0.421	0.438	4	TiN
1735401	●	3/8 - 18 NPT	2.563	1.091	1.346	0.700	0.531	0.500	4	Steam Oxide
1735405	●	3/8 - 18 NPT	2.563	1.091	1.346	0.700	0.531	0.500	4	TiN
1735501	●	1/2 - 14 NPT	3.126	1.409	-	0.688	0.515	0.625	4	Steam Oxide
1735505	●	1/2 - 14 NPT	3.126	1.409	-	0.688	0.515	0.625	4	TiN
1744805	●	3/4 - 14 NPT	3.252	1.374	-	0.906	0.679	0.688	4	TiN
1735601	●	3/4 - 14 NPT	3.252	1.374	-	0.906	0.679	0.688	5	Steam Oxide
1744905	●	1 - 11.5 NPT	3.752	1.752	-	1.125	0.843	0.813	4	TiN
1735701	●	1 - 11.5 NPT	3.752	1.752	-	1.125	0.843	0.813	5	Steam Oxide

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

**EXT**

ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

P					M			K	N		S		H					
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel					
Carbon Steel			Alloy Steel	Die Steel	Aluminum		Nickel Alloy		Titanium									
Low	Medium	High			6061	7075				Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC		
1010	1035	1065	4140	4340	300	400	17-4 PH											
○	○				⊗	⊗	⊗											
15-40 SFM	10-25 SFM				10-25 SFM	10-25 SFM	8-12 SFM											

○ Good ⊗ Best

