




List 312Ti

EXOTAP® VC-10 V-TI-POT

SPIRAL POINT	VC10	V	C/SP	0°	PACKED 1 PIECE
--------------	------	---	------	----	-------------------



EDP		Thread Size	Thread Limit	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Number of Flutes
				L (Inch)	Lc (Inch)	L1 (Inch)	d (Inch)	k (Inch)	lk (Inch)	
1105610108	●	No. 2 - 56 UNC	H2	1.752	0.437	-	0.141	0.110	0.188	2
1105610208	●	No. 4 - 40 UNC	H2	1.874	0.562	-	0.141	0.110	0.188	3
1105610408	●	No. 6 - 32 UNC	H2	2.000	0.688	-	0.141	0.110	0.188	3
1105610508	●	No. 6 - 32 UNC	H3	2.000	0.688	-	0.141	0.110	0.188	3
1105610608	●	No. 6 - 40 UNF	H2	2.000	0.688	-	0.141	0.110	0.188	3
1105610708	●	No. 8 - 32 UNC	H2	2.126	0.751	-	0.168	0.131	0.250	3
1105610808	●	No. 8 - 32 UNC	H3	2.126	0.751	-	0.168	0.131	0.250	3
1105610908	●	No. 8 - 36 UNF	H2	2.126	0.751	-	0.168	0.131	0.250	3
1105611008	●	No. 10 - 24 UNC	H3	2.374	0.874	-	0.194	0.152	0.250	3
1105611108	●	No. 10 - 32 UNF	H2	2.374	0.866	-	0.194	0.152	0.250	3
1105611208	●	No. 10 - 32 UNF	H3	2.374	0.866	-	0.194	0.152	0.250	3
1105611308	●	1/4 - 20 UNC	H3	2.500	1.000	-	0.255	0.191	0.313	3
1105611408	●	1/4 - 20 UNC	H5	2.500	1.000	-	0.255	0.191	0.313	3
1105611508	●	1/4 - 28 UNF	H3	2.500	0.988	-	0.255	0.191	0.313	3
1105611608	●	1/4 - 28 UNF	H4	2.500	0.988	-	0.255	0.191	0.313	3
1105611708	●	5/16 - 18 UNC	H3	2.720	0.665	1.125	0.318	0.238	0.375	3
1105611808	●	5/16 - 18 UNC	H5	2.720	0.665	1.125	0.318	0.238	0.375	3
1105611908	●	5/16 - 24 UNF	H3	2.720	0.657	1.118	0.318	0.238	0.375	3
1105612008	●	5/16 - 24 UNF	H4	2.720	0.657	1.118	0.318	0.238	0.375	3
1105612108	●	3/8 - 16 UNC	H3	2.937	0.751	1.251	0.381	0.286	0.438	3
1105612208	●	3/8 - 16 UNC	H5	2.937	0.751	1.251	0.381	0.286	0.438	3
1105612308	●	3/8 - 24 UNF	H3	2.937	0.740	1.240	0.381	0.286	0.438	3
1105612408	●	3/8 - 24 UNF	H4	2.937	0.740	1.240	0.381	0.286	0.438	3
1105612508	●	7/16 - 14 UNC	H3	3.157	0.858	1.291	0.323	0.242	0.406	3
1105612608	●	7/16 - 14 UNC	H5	3.157	0.858	1.291	0.323	0.242	0.406	3
1105612708	●	7/16 - 20 UNF	H3	3.157	0.858	1.291	0.323	0.242	0.406	3
1105612808	●	7/16 - 20 UNF	H5	3.157	0.858	1.291	0.323	0.242	0.406	3
1105612908	●	1/2 - 13 UNC	H3	3.374	0.921	1.354	0.367	0.275	0.438	3
1105613008	●	1/2 - 13 UNC	H5	3.374	0.921	1.354	0.367	0.275	0.438	3
1105613108	●	1/2 - 20 UNF	H3	3.374	0.921	1.354	0.367	0.275	0.438	3
1105613208	●	1/2 - 20 UNF	H5	3.374	0.921	1.354	0.367	0.275	0.438	3
1105613308	●	9/16 - 18 UNF	H3	3.594	1.000	1.472	0.429	0.322	0.500	3
1105613408	●	9/16 - 18 UNF	H5	3.594	1.000	1.472	0.429	0.322	0.500	3
1105613508	●	5/8 - 11 UNC	H3	3.811	1.090	1.562	0.480	0.360	0.563	3
1105613608	●	5/8 - 18 UNF	H3	3.811	1.090	1.562	0.480	0.360	0.563	3
1105613708	●	5/8 - 18 UNF	H5	3.811	1.090	1.562	0.480	0.360	0.563	3
1105613808	●	3/4 - 10 UNC	H5	4.252	1.200	1.712	0.590	0.442	0.688	4
1105613908	●	3/4 - 16 UNF	H3	4.252	1.200	1.712	0.590	0.442	0.688	4
1105614008	●	3/4 - 16 UNF	H5	4.252	1.200	1.712	0.590	0.442	0.688	4
1105614208	●	7/8 - 9 UNC	H3	4.689	1.334	1.885	0.697	0.523	0.750	4
1105614308	●	7/8 - 9 UNC	H5	4.689	1.334	1.885	0.697	0.523	0.750	4
1105614408	●	7/8 - 14 UNF	H3	4.689	1.334	1.885	0.697	0.523	0.750	4
1105614508	●	7/8 - 14 UNF	H5	4.689	1.334	1.956	0.697	0.523	0.750	4
1105614108	●	1 - 8 UNC	H5	5.126	1.500	2.090	0.800	0.600	0.813	4

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

EXT

P					M			K Cast Iron	N		S		H							
Steel					Stainless Steel				Non-Ferrous		HRSA		Hardened Steel							
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium								
Low	Medium	High			300	400	17-4 PH		6061 7075	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC				
1010	1035	1065	4140																	
1018	1045		4340																	
			15-30 SFM				8-20 SFM													

○ Good ⊗ Best

