



## List 313Ti

EXOTAP® VC-10 V-Ti-SFT

SPIRAL FLUTE	VC10	V	C/2.5P	10°	PACKED 1 PIECE
--------------	------	---	--------	-----	-------------------



EDP Number	Thread Size	Thread Limit	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Number of Flutes
			L (Inch)	Lc (Inch)	L1 (Inch)	d (Inch)	k (Inch)	lk (Inch)	
1305710108	No. 2 - 56 UNC	H2	1.750	0.437	-	0.141	0.110	0.188	3
1305710208	No. 4 - 40 UNC	H2	1.875	0.559	-	0.141	0.110	0.188	3
1305710408	No. 6 - 32 UNC	H2	2.000	0.685	-	0.141	0.110	0.188	3
1305710508	No. 6 - 32 UNC	H3	2.000	0.685	-	0.141	0.110	0.188	3
1305710608	No. 6 - 40 UNF	H2	2.000	0.685	-	0.141	0.110	0.188	3
1305710708	No. 8 - 32 UNC	H2	2.125	0.752	-	0.168	0.131	0.250	3
1305710808	No. 8 - 32 UNC	H3	2.125	0.752	-	0.168	0.131	0.250	3
1305710908	No. 8 - 36 UNF	H2	2.125	0.752	-	0.168	0.131	0.250	3
1305711008	No. 10 - 24 UNC	H3	2.375	0.866	-	0.194	0.152	0.250	3
1305711108	No. 10 - 32 UNF	H2	2.375	0.866	-	0.194	0.152	0.250	3
1305711208	No. 10 - 32 UNF	H3	2.375	0.866	-	0.194	0.152	0.250	3
1305711308	1/4 - 20 UNC	H3	2.500	0.996	-	0.255	0.191	0.313	3
1305711408	1/4 - 20 UNC	H5	2.500	0.996	-	0.255	0.191	0.313	3
1305711508	1/4 - 28 UNF	H3	2.500	0.996	-	0.255	0.191	0.313	3
1305711608	1/4 - 28 UNF	H4	2.500	0.996	-	0.255	0.191	0.313	3
1305714608	1/4 - 28 UNF	H5	2.500	0.996	-	0.255	0.191	0.313	3
1305711708	5/16 - 18 UNC	H3	2.719	0.445	1.126	0.318	0.238	0.375	3
1305711808	5/16 - 18 UNC	H5	2.719	0.445	1.126	0.318	0.238	0.375	3
1305711908	5/16 - 24 UNF	H3	2.719	0.445	1.126	0.318	0.238	0.375	3
1305712008	5/16 - 24 UNF	H4	2.719	0.445	1.126	0.318	0.238	0.375	3
1305712108	3/8 - 16 UNC	H3	2.938	0.500	1.252	0.381	0.286	0.438	3
1305712208	3/8 - 16 UNC	H5	2.938	0.500	1.252	0.381	0.286	0.438	3
1305712308	3/8 - 24 UNF	H3	2.938	0.500	1.252	0.381	0.286	0.438	3
1305712408	3/8 - 24 UNF	H4	2.938	0.500	1.252	0.381	0.286	0.438	3
1305712508	7/16 - 14 UNC	H3	3.156	0.571	1.713	0.323	0.242	0.406	3
1305712608	7/16 - 14 UNC	H5	3.156	0.571	1.713	0.323	0.242	0.406	3
1305712708	7/16 - 20 UNF	H3	3.156	0.571	1.713	0.323	0.242	0.406	3
1305712808	7/16 - 20 UNF	H5	3.156	0.571	1.713	0.323	0.242	0.406	3
1305712908	1/2 - 13 UNC	H3	3.375	0.614	1.933	0.367	0.275	0.438	3
1305713008	1/2 - 13 UNC	H5	3.375	0.614	1.933	0.367	0.275	0.438	3
1305713108	1/2 - 20 UNF	H3	3.375	0.614	1.933	0.367	0.275	0.438	3
1305713208	1/2 - 20 UNF	H5	3.375	0.614	1.933	0.367	0.275	0.438	3
1305713308	9/16 - 18 UNF	H3	3.594	0.665	1.972	0.429	0.322	0.500	4
1305713408	9/16 - 18 UNF	H5	3.594	0.665	1.972	0.429	0.322	0.500	4
1305713508	5/8 - 11 UNC	H3	3.813	0.728	2.126	0.480	0.360	0.563	4
1305713608	5/8 - 18 UNF	H3	3.813	0.728	2.126	0.480	0.360	0.563	4
1305713708	5/8 - 18 UNF	H5	3.813	0.728	2.126	0.480	0.360	0.563	4
1305713808	3/4 - 10 UNC	H5	4.250	0.799	2.433	0.590	0.442	0.688	4
1305713908	3/4 - 16 UNF	H3	4.250	0.799	2.433	0.590	0.442	0.688	4
1305714008	3/4 - 16 UNF	H5	4.250	0.799	2.433	0.590	0.442	0.688	4
1305714208	7/8 - 9 UNC	H3	4.688	0.890	2.654	0.697	0.523	0.750	4
1305714308	7/8 - 9 UNC	H5	4.688	0.890	2.654	0.697	0.523	0.750	4
1305714408	7/8 - 14 UNF	H3	4.688	0.890	2.654	0.697	0.523	0.750	4
1305714508	7/8 - 14 UNF	H5	4.688	0.890	2.654	0.697	0.523	0.750	4
1305714108	1 - 8 UNC	H5	5.125	1.000	3.012	0.800	0.600	0.813	4

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

EXT

P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel	300	400	17-4 PH		Aluminum		Nickel Alloy	Titanium	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
Low	Medium	High							6061	Casting						
1010	1035	1065	4140					7075								
1018	1045		4340													
			15-30 SFM				8-20 SFM									

○ Good ⊗ Best

