




## List 320

EXOTAP® TIN-POT

SPIRAL POINT	HSSE	TiN	C/4P	0°	PACKED 1 PIECE
--------------	------	-----	------	----	-------------------



EDP	Flute	Thread Size	Thread Limit	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Number of Flutes
				L (Inch)	Lc (Inch)	L1 (Inch)	d (Inch)	k (Inch)	lk (Inch)	
1740005	●	No. 4 - 40 UNC	H2	1.874	0.295	0.559	0.141	0.110	0.188	2
1740105	●	No. 5 - 40 UNC	H2	1.937	0.299	0.626	0.141	0.110	0.188	2
1740205	●	No. 6 - 32 UNC	H3	2.000	0.370	0.685	0.141	0.110	0.188	2
1742005	●	No. 6 - 32 UNC	H5	2.000	0.370	0.685	0.141	0.110	0.188	2
1742105	●	No. 6 - 32 UNC	H7	2.000	0.370	0.685	0.141	0.110	0.188	2
1740305	●	No. 8 - 32 UNC	H3	2.126	0.374	0.752	0.168	0.131	0.250	3
1740405	●	No. 10 - 24 UNC	H3	2.374	0.492	0.866	0.194	0.152	0.250	3
1740505	●	No. 10 - 32 UNF	H3	2.374	0.492	0.866	0.194	0.152	0.250	3
1742205	●	No. 10 - 32 UNF	H5	2.374	0.492	0.866	0.194	0.152	0.250	3
1742305	●	No. 10 - 32 UNF	H7	2.374	0.492	0.866	0.194	0.152	0.250	3
1740605	●	1/4 - 20 UNC	H3	2.500	0.594	0.996	0.255	0.191	0.313	3
1740705	●	1/4 - 28 UNF	H3	2.500	0.594	0.996	0.255	0.191	0.313	3
1742405	●	1/4 - 28 UNF	H5	2.500	0.594	0.996	0.255	0.191	0.313	3
1742505	●	1/4 - 28 UNF	H7	2.500	0.594	0.996	0.255	0.191	0.313	3
1740805	●	5/16 - 18 UNC	H3	2.720	0.665	1.126	0.318	0.238	0.375	3
1740905	●	5/16 - 24 UNF	H3	2.720	0.657	1.118	0.318	0.238	0.375	3
1742605	●	5/16 - 24 UNF	H5	2.720	0.657	1.118	0.318	0.238	0.375	3
1742705	●	5/16 - 24 UNF	H7	2.720	0.657	1.118	0.318	0.238	0.375	3
1741005	●	3/8 - 16 UNC	H3	2.937	0.752	1.252	0.381	0.286	0.438	3
1741105	●	3/8 - 24 UNF	H3	2.937	0.740	1.240	0.381	0.286	0.438	3
1742805	●	3/8 - 24 UNF	H5	2.937	0.740	1.240	0.381	0.286	0.438	3
1742905	●	3/8 - 24 UNF	H7	2.937	0.740	1.240	0.381	0.286	0.438	3
1741205	●	7/16 - 14 UNC	H3	2.937	0.858	1.291	0.323	0.242	0.406	3
1741305	●	7/16 - 20 UNF	H3	3.157	0.858	1.291	0.323	0.242	0.406	3
1741405	●	1/2 - 13 UNC	H3	3.157	0.921	1.354	0.367	0.275	0.438	3
1741505	●	1/2 - 20 UNF	H3	3.374	0.921	1.354	0.367	0.275	0.438	3
1741605	●	5/8 - 11 UNC	H3	3.374	1.091	1.563	0.480	0.360	0.563	3
1741705	●	5/8 - 18 UNF	H3	3.811	1.091	1.563	0.480	0.360	0.563	3
1741805	●	3/4 - 10 UNC	H3	3.811	1.201	1.713	0.590	0.442	0.688	3
1741905	●	3/4 - 16 UNF	H3	4.252	1.201	1.713	0.590	0.442	0.688	3

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

EXT

P					M			K	N		S		H				
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel				
Carbon Steel			Alloy Steel	Die Steel	Aluminum		Nickel Alloy		Titanium								
Low	Medium	High			6061	7075				Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC	
1010	1035	1065	4140	4340	300	400	17-4 PH		6061	7075	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
○	○	⊙	⊙	⊙	○	○	○	○	○	○				○			
25-80 SFM	20-50 SFM	20-45 SFM	20-50 SFM	15-20 SFM	20-45 SFM	15-20 SFM	8-20 SFM	25-75 SFM	40-80 SFM	40-65 SFM				15-35 SFM			

○ Good ⊙ Best

