



List 344STI

EXOTAP® VC-10 POT STI

SPIRAL POINT	VC10	S/O	V	C/SP	0°	STI	PACKED 1 PIECE
--------------	------	-----	---	------	----	-----	-------------------



EDP		Thread Size	Thread Limit	Overall Length	Thread Length	Neck Length	Shank Diameter	Square Width	Square Length	Number of Flutes	Surface Treatment
				L (mm)	Lc (mm)	L1 (mm)	d (mm)	k (mm)	lk (mm)		
34400101	●	M2 x 0.4	D2	48.59	12.65	-	3.58	2.79	4.76	2	Steam Oxide
34400108	●	M2 x 0.4	D2	48.59	12.65	-	3.58	2.79	4.76	2	V
34400201	●	M2.5 x 0.45	D2	49.30	6.30	15.90	3.58	2.79	4.76	2	Steam Oxide
34400208	●	M2.5 x 0.45	D2	49.30	6.30	15.90	3.58	2.79	4.76	2	V
34400301	●	M3 x 0.5	D2	50.80	7.21	17.70	3.58	2.79	4.76	3	Steam Oxide
34400308	●	M3 x 0.5	D2	50.80	7.21	17.70	3.58	2.79	4.76	3	V
34400401	●	M4 x 0.7	D3	60.50	9.93	22.35	4.93	3.86	6.35	3	Steam Oxide
34400408	●	M4 x 0.7	D3	60.50	9.93	22.35	4.93	3.86	6.35	3	V
34400501	●	M5 x 0.8	D3	63.50	11.38	25.58	6.48	4.85	7.94	3	Steam Oxide
34400508	●	M5 x 0.8	D3	63.50	11.38	25.58	6.48	4.85	7.94	3	V
34400601	●	M6 x 1	D3	69.09	14.22	28.83	8.08	6.05	9.53	3	Steam Oxide
34400608	●	M6 x 1	D3	69.09	14.22	28.83	8.08	6.05	9.53	3	V
34400701	●	M8 x 1.25	D3	74.70	17.91	32.00	9.68	7.26	11.11	3	Steam Oxide
34400708	●	M8 x 1.25	D3	74.70	17.91	32.00	9.68	7.26	11.11	3	V
34400801	●	M10 x 1.5	D4	85.90	21.01	32.00	9.32	6.99	11.11	3	Steam Oxide
34400808	●	M10 x 1.5	D4	85.90	21.01	32.00	9.32	6.99	11.11	3	V
34400901	●	M12 x 1.75	D4	91.21	24.51	36.50	10.90	8.18	12.70	3	Steam Oxide
34400908	●	M12 x 1.75	D4	91.21	24.51	36.50	10.90	8.18	12.70	3	V
34401001	●	M14 x 2	D5	102.39	27.99	41.00	13.77	10.31	15.88	4	Steam Oxide
34401008	●	M14 x 2	D5	102.39	27.99	41.00	13.77	10.31	15.88	4	V
34401101	●	M16 x 2	D5	108.00	27.99	42.01	14.99	11.23	17.46	4	Steam Oxide
34401108	●	M16 x 2	D5	108.00	27.99	42.01	14.99	11.23	17.46	4	V
34401201	●	M18 x 2.5	D5	119.10	35.00	49.00	17.70	13.28	19.05	4	Steam Oxide
34401208	●	M18 x 2.5	D5	119.10	35.00	49.00	17.70	13.28	19.05	4	V
34401301	●	M20 x 2.5	D5	124.61	35.00	50.01	19.30	14.48	19.05	4	Steam Oxide
34401308	●	M20 x 2.5	D5	124.61	35.00	50.01	19.30	14.48	19.05	4	V
34401401	●	M22 x 2.5	D5	130.20	35.00	50.01	20.32	15.24	20.64	4	Steam Oxide
34401408	●	M22 x 2.5	D5	130.20	35.00	50.01	20.32	15.24	20.64	4	V
34401501	●	M24 x 3	D6	138.10	42.01	57.99	22.76	17.07	22.23	4	Steam Oxide
34401508	●	M24 x 3	D6	138.10	42.01	57.99	22.76	17.07	22.23	4	V

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

EXT

P					M			K	N		S		H				
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel				
Carbon Steel			Alloy Steel	Die Steel	Aluminum		Nickel Alloy		Titanium								
Low	Medium	High			6061	Casting				Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC		
1010	1035	1065	4140		300	400	17-4 PH	6061	7075								
			15-30 SFM	10-25 SFM		12-45 SFM	8-20 SFM					8-15 SFM	8-15 SFM	15-35 SFM	10-20 SFM		

○ Good ⊙ Best

