List 345

EXOTAP® VC-10 SFT

SPIRAL FLUTE | VC10 | S/0 | V | 3 FLUTE | C/2.5P | 15° | PACKED 1 PIECE



EDP Number		Thread Size	Thread Limit	Overall Length L (mm)	Thread Length Lc (mm)	Neck Length L1 (mm)	Shank Diameter d (mm)	Square Width k (mm)	Square Length lk (mm)	Number of Flutes	Surface Treatment
1705501	●	M3 x 0.5	D3	49.20	4.10	16.00	3.58	2.79	4.76	3	Steam Oxide
1705508	●	M3 x 0.5	D3	49.20	4.10	16.00	3.58	2.79	4.76	3	V
1705601	●	M4 x 0.7	D4	54.00	5.60	19.10	4.27	3.33	6.35	3	Steam Oxide
1705608	●	M4 x 0.7	D4	54.00	5.60	19.10	4.27	3.33	6.35	3	V
1705701	●	M5 x 0.8	D4	60.30	6.40	22.20	4.93	3.86	6.35	3	Steam Oxide
1705708	●	M5 x 0.8	D4	60.30	6.40	22.20	4.93	3.86	6.35	3	V
1705801	●	M6 x 1	D5	63.50	8.00	25.40	6.48	4.85	7.94	3	Steam Oxide
1705808	●	M6 x 1	D5	63.50	8.00	25.40	6.48	4.85	7.94	3	V
1705901	●	M8 x 1.25	D5	69.10	10.00	28.60	8.08	6.05	9.53	3	Steam Oxide
1705908	●	M8 x 1.25	D5	69.10	10.00	28.60	8.08	6.05	9.53	3	V
1706001	●	M10 x 1.25	D5	74.60	12.00	31.80	9.68	7.26	11.11	3	Steam Oxide
1706008	●	M10 x 1.25	D5	74.60	12.00	31.80	9.68	7.26	11.11	3	V
1706101	●	M10 x 1.5	D6	74.60	12.00	31.80	9.68	7.26	11.11	3	Steam Oxide
1706108	●	M10 x 1.5	D6	74.60	12.00	31.80	9.68	7.26	11.11	3	V
1706201	●	M12 x 1.75	D6	85.70	14.00	49.10	9.32	6.99	11.11	3	Steam Oxide
1706208	●	M12 x 1.75	D6	85.70	14.00	49.10	9.32	6.99	11.11	3	V

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

EXT

P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium				
Low	Medium	High														
1010 1018	1035 1045	1065	4140 4340		300	400	17-4 PH		6061 7075	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
			◎	○		○	◎				○	○	◎	○		
			15-30 SFM	10-25 SFM		12-45 SFM	8-20 SFM				8-15 SFM	8-15 SFM	15-35 SFM	10-20 SFM		

○ Good ◎ Best