



List 356

EXOCARB® LT-OTT, JIS

STRAIGHT FLUTE	CARBIDE	BR	C/1.5P	C/3P	0°	PACKED 1 PIECE
----------------	---------	----	--------	------	----	-------------------



EDP	Thread Size	Thread Limit	Overall Length	Thread Length	Shank Diameter	Square Width	Square Length	Number of Flutes
			L (mm)	Lc (mm)	d (mm)	k (mm)	lk (mm)	
22929	● M6 x 1	OH3	100.00	24.00	6.00	4.50	7.00	3
22933	● M8 x 1.25	OH4	150.00	22.00	6.20	5.00	8.00	4
22949	● M10 x 1	OH4	150.00	24.00	7.00	5.50	8.00	4
22945	● M10 x 1.25	OH4	150.00	24.00	7.00	5.50	8.00	4
22941	● M10 x 1.5	OH4	150.00	24.00	7.00	5.50	8.00	4
22953	● M12 x 1.75	OH4	150.00	29.00	8.50	6.50	9.00	4

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked
 Note: Other coatings are available upon request.



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

P					M			K	N				S		Other			
Steel					Stainless Steel			Cast Iron	Non-Ferrous				HRSA		Fiberglass	Cobalt-Chrome	Thermo-Plastics	Thermo-setting Plastics
Carbon Steel			Alloy Steel	Die Steel	300	400	17-4 PH		Aluminum		MMC (Metal Matrix Composites)	Copper Alloys	Nickel Alloy	Titanium				
Low	Medium	High							6061	7075								
1010	1035	1065	4140	4340				○	○	○	○			○	○			
1018	1045							40-90 SFM	60-160 SFM	55-120 SFM		40-80 SFM		30-60 SFM	15-40 SFM			

○ Good ○ Best

