



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

List 3620

EXOCARB® WXL®-2D-DE



SPEED FEED
1357

CARBIDE

WXL

2 FLUTE

30°



SHANK
h6

REG

PACKED
1 PIECE

Cutting Diameter Tolerance	
1/16" ≤ D ≤ 7/16"	+0 / -0.0008"
1/2" ≤ D ≤ 3/4"	+0 / -0.0012"



EDP Number	Diameter	Length of Cut	Overall Length	Shank Diameter
36200001	1/16	0.125	2.000	0.125
36200002	5/64	0.156	2.000	0.125
36200003	3/32	0.188	2.000	0.125
36200004	7/64	0.219	2.000	0.125
36200005	1/8	0.250	2.000	0.125
36200006	5/32	0.313	2.000	0.188
36200007	3/16	0.375	2.000	0.188
36200008	7/32	0.438	2.000	0.250
36200009	1/4	0.500	2.500	0.250
36200010	9/32	0.563	2.500	0.313
36200011	5/16	0.625	2.500	0.313
36200012	3/8	0.750	2.750	0.375
36200013	7/16	0.875	3.000	0.438
36200014	1/2	1.000	3.000	0.500
36200015	5/8	1.250	3.500	0.625
36200016	3/4	1.500	4.000	0.750

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H				
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel				
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium					
Low	Medium	High			300	400	17-4 PH		6061 7075	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC
1010	1035	1065	4140	4340	○	○	○	○	○	○	○	○	○	○	○	○	○
1018	1045				○	○	○	○	○	○	○	○	○	○	○	○	○

○ Good ○ Best

