



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

List 3621

EXOCARB® WXL®-3D-DE



SPEED FEED
1357

CARBIDE

WXL

2 FLUTE

35°



SHANK
h6

REG

PACKED
1 PIECE



Cutting Diameter Tolerance	
1/16" ≤ D ≤ 7/16"	+0 / -0.0008"
1/2" ≤ D ≤ 3/4"	+0 / -0.0012"

EDP Number		Diameter		Length of Cut	Overall Length	Shank Diameter
		D (Fractional Size)	Lc (Inch)	L (Inch)	d (Inch)	
36210001	●	1/16	0.188	2.000	0.125	
36210002	●	5/64	0.234	2.000	0.125	
36210003	●	3/32	0.281	2.000	0.125	
36210004	●	7/64	0.328	2.000	0.125	
36210005	●	1/8	0.375	2.000	0.125	
36210006	●	5/32	0.469	2.000	0.188	
36210007	●	3/16	0.563	2.250	0.188	
36210008	●	7/32	0.656	2.500	0.250	
36210009	●	1/4	0.750	2.500	0.250	
36210010	●	9/32	0.844	2.750	0.313	
36210011	●	5/16	0.938	2.750	0.313	
36210012	●	3/8	1.125	3.000	0.375	
36210013	●	7/16	1.313	3.250	0.438	
36210014	●	1/2	1.500	3.500	0.500	
36210015	●	5/8	1.875	4.250	0.625	
36210016	●	3/4	2.250	5.000	0.750	

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H						
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel						
Carbon Steel			Alloy Steel	Die Steel	Aluminum		Nickel Alloy		Titanium	Hardened Steel									
Low	Medium	High			6061	Casting				Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC				
1010	1035	1065	4140	4340	300	400	17-4 PH	6061	7075	○	○	○	○	○	○	○	○	○	○
○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

○ Good ○ Best

