



## List 3710

EXOCARB® WXL-EBD



SPEED FEED  
1476

CARBIDE

WXL



30°



SHANK  
h6

STUB

REG

PACKED  
1 PIECE



Radius Tolerance	
0.1mm ≤ D ≤ 5mm	+/- 0.005mm
6mm ≤ D ≤ 12mm	+0.003 / -0.007mm
14mm ≤ D ≤ 20mm	+/- 0.010mm

EDP Number	Diameter	Length of Cut	Overall Length	Shank Diameter
3105010	0.10	0.20	40.00	4.00
3105020	0.20	0.40	40.00	4.00
3105030	0.30	0.60	40.00	4.00
3105040	0.40	0.80	40.00	4.00
3105050	0.50	1.10	40.00	4.00
3105060	0.60	1.10	40.00	4.00
3105080	0.80	2.00	40.00	4.00
3105100	1.00	1.50	50.00	4.00
3106100	1.00	2.50	60.00	6.00
3105120	1.20	3.00	50.00	4.00
3105140	1.40	3.50	50.00	4.00
3105150	1.50	2.00	50.00	4.00
3106150	1.50	4.00	50.00	6.00
3105160	1.60	4.00	50.00	4.00
3105200	2.00	3.00	50.00	4.00
3106200	2.00	5.00	50.00	6.00
3105250	2.50	3.00	50.00	4.00
3106250	2.50	6.00	60.00	6.00
3105300	3.00	4.50	60.00	4.00
3106301	3.00	8.00	60.00	6.00
3106350	3.50	8.00	70.00	6.00
3106400	4.00	6.00	70.00	6.00
3105400	4.00	8.00	60.00	4.00
3106500	5.00	8.00	80.00	6.00
3106502	5.00	12.00	80.00	6.00
3106600	6.00	10.00	90.00	6.00
3106601	6.00	12.00	90.00	6.00
3106610	7.00	14.00	90.00	6.00
3106620	8.00	12.00	100.00	8.00
3106621	8.00	14.00	100.00	8.00
3106630	9.00	18.00	100.00	8.00
3106640	10.00	15.00	100.00	10.00
3106641	10.00	18.00	100.00	10.00
3106650	11.00	22.00	100.00	10.00
3106660	12.00	18.00	110.00	12.00
3106661	12.00	22.00	110.00	12.00
3106670	14.00	26.00	110.00	12.00
3106680	16.00	30.00	140.00	16.00
3106690	18.00	34.00	140.00	16.00
3106700	20.00	38.00	160.00	20.00

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel	300	400	17-4 PH		Aluminum		Nickel Alloy	Titanium	Hardened Steel			
Low	Medium	High							6061	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
1010	1035	1065	4140	4340	300	400	17-4 PH	6061	7075	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

○ Good ○ Best

