



List 3711

EXOCARB® WXL-LS-EBD, Long Shank



SPEED FEED
1481

CARBIDE
WXL

2 FLUTE

30°



SHANK
h6

STUB

REG

PACKED
1 PIECE

Radius Tolerance	
1mm ≤ D ≤ 5mm	+/- 0.005mm
6mm ≤ D ≤ 18mm	+/- 0.010mm



EDP Number	Diameter	Length of Cut	Overall Length	Shank Diameter
37110000	1.00	2.50	70.00	3.00
37110001	2.00	5.00	70.00	3.00
37110002	3.00	8.00	80.00	3.00
37110003	4.00	8.00	100.00	4.00
37110004	5.00	10.00	100.00	4.00
37110005	6.00	12.00	140.00	6.00
37110006	7.00	14.00	140.00	6.00
37110007	8.00	14.00	160.00	8.00
37110008	10.00	18.00	180.00	10.00
37110009	12.00	22.00	200.00	12.00
37110010	14.00	26.00	200.00	12.00
37110011	16.00	30.00	220.00	16.00
37110012	18.00	34.00	220.00	16.00

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H					
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel					
Carbon Steel			Alloy Steel	Die Steel	Aluminum		Nickel Alloy		Titanium	Hardened Steel								
Low	Medium	High			6061	7075				Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC		
1010	1035	1065	4140	4340	300	400	17-4 PH	○	○	○	○	○	○	○	○	○	○	○
○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

○ Good ○ Best

