



## List 3742

EXOCARB® WXL®-EML



SPEED FEED  
1372

CARBIDE

WXL

4 FLUTE

30°



SHANK  
h6

REG

LONG

PACKED  
1 PIECE

Cutting Diameter Tolerance	
3mm ≤ D ≤ 26mm	+0 / -0.030mm



EDP Number		Diameter	Length of Cut	Overall Length	Shank Diameter
		D (mm)	Lc (mm)	L (mm)	d (mm)
37420000	●	3.00	12.00	50.00	6.00
37420001	●	3.50	14.00	50.00	6.00
37420002	●	4.00	17.00	50.00	6.00
37420003	●	4.50	17.00	50.00	6.00
37420004	●	5.00	20.00	60.00	6.00
37420005	●	5.50	20.00	60.00	6.00
37420006	●	6.00	20.00	60.00	6.00
37420007	●	6.50	24.00	70.00	8.00
37420008	●	7.00	24.00	70.00	8.00
37420009	●	7.50	24.00	70.00	8.00
37420010	●	8.00	28.00	70.00	8.00
37420011	●	8.50	28.00	80.00	10.00
37420012	●	9.00	28.00	80.00	10.00
37420013	●	9.50	28.00	80.00	10.00
37420014	●	10.00	34.00	80.00	10.00
37420015	●	10.50	34.00	90.00	12.00
37420016	●	11.00	34.00	90.00	12.00
37420017	●	11.50	34.00	90.00	12.00
37420018	●	12.00	40.00	90.00	12.00
37420019	●	13.00	40.00	100.00	12.00
37420020	●	14.00	40.00	100.00	12.00
37420021	●	15.00	40.00	105.00	16.00
37420022	●	16.00	48.00	115.00	16.00
37420023	●	18.00	48.00	115.00	16.00
37420024	●	20.00	56.00	125.00	20.00
37420025	●	23.00	67.00	140.00	25.00
37420026	●	24.00	67.00	140.00	25.00
37420027	●	25.00	67.00	140.00	25.00
37420028	●	26.00	67.00	140.00	25.00

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel	300	400	17-4 PH		Aluminum		Nickel Alloy	Titanium	Hardened Steel			
Low	Medium	High							6061	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
1010	1035	1065	4140	4340	300	400	17-4 PH	6061	7075	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

○ Good ○ Best

