



List 3770

EXOCARB® WXL-CR-EDS



SPEED FEED
1435

CARBIDE

WXL



Cutting Diameter Tolerance	
0.6mm ≤ D ≤ 12mm	+0 / -0.020mm




EDP Number		Diameter	Corner Radius	Length of Cut	Neck Length	Neck Diameter	Overall Length	Shank Diameter	Type
		D (mm)	R (mm)	Lc (mm)	L1 (mm)	d1 (mm)	L (mm)	d (mm)	
37700000	●	0.60	0.10	0.90	2.00	0.55	50.00	6.00	1
37700001	●	0.80	0.10	1.20	2.60	0.75	50.00	6.00	1
37700002	●	1.00	0.10	1.50	2.70	0.95	50.00	6.00	1
37700003	●	1.20	0.10	1.80	3.20	1.15	50.00	6.00	1
37700004	●	1.40	0.10	2.10	3.70	1.35	50.00	6.00	1
37700005	●	1.50	0.10	2.30	4.00	1.45	50.00	6.00	1
37700006	●	1.60	0.10	2.40	4.20	1.55	50.00	6.00	1
37700007	●	1.80	0.10	2.70	4.70	1.75	50.00	6.00	1
37700008	●	2.00	0.10	3.00	5.20	1.95	50.00	6.00	1
37700009	●	2.50	0.10	3.70	5.20	2.40	50.00	6.00	1
37700010	●	3.00	0.20	8.00	-	-	60.00	6.00	2
37700011	●	3.00	0.50	8.00	-	-	60.00	6.00	2
37700012	●	4.00	0.20	11.00	-	-	70.00	6.00	2
37700013	●	4.00	0.50	11.00	-	-	70.00	6.00	2
37700014	●	4.00	1.00	11.00	-	-	70.00	6.00	2
37700015	●	5.00	0.20	13.00	-	-	80.00	6.00	2
37700016	●	5.00	0.50	13.00	-	-	80.00	6.00	2
37700017	●	5.00	1.00	13.00	-	-	80.00	6.00	2
37700018	●	6.00	0.20	13.00	-	-	90.00	6.00	3
37700019	●	6.00	0.50	13.00	-	-	90.00	6.00	3
37700020	●	6.00	1.00	13.00	-	-	90.00	6.00	3
37700021	●	6.00	1.50	13.00	-	-	90.00	6.00	3
37700022	●	6.00	2.00	13.00	-	-	90.00	6.00	3
37700023	●	8.00	0.50	19.00	-	-	100.00	8.00	3
37700024	●	8.00	1.00	19.00	-	-	100.00	8.00	3
37700025	●	8.00	1.50	19.00	-	-	100.00	8.00	3
37700026	●	8.00	2.00	19.00	-	-	100.00	8.00	3
37700027	●	10.00	0.50	22.00	-	-	100.00	10.00	3
37700028	●	10.00	1.00	22.00	-	-	100.00	10.00	3
37700029	●	10.00	1.50	22.00	-	-	100.00	10.00	3
37700030	●	10.00	2.00	22.00	-	-	100.00	10.00	3
37700031	●	10.00	3.00	22.00	-	-	100.00	10.00	3
37700032	●	12.00	0.50	26.00	-	-	110.00	12.00	3
37700033	●	12.00	1.00	26.00	-	-	110.00	12.00	3
37700034	●	12.00	1.50	26.00	-	-	110.00	12.00	3
37700035	●	12.00	2.00	26.00	-	-	110.00	12.00	3
37700036	●	12.00	3.00	26.00	-	-	110.00	12.00	3


● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked




Type 1



Type 2



Type 3



P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Low	Medium	High	Alloy Steel	Die Steel	300	400	17-4 PH		Aluminum	Nickel Alloy	Titanium	Hardened Steel				
1010 1018	1035 1045	1065	4140 4340					6061 7075	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC	
○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	

○ Good ○ Best

