



## List 3791

EXOCARB® WXL®-LN-EDS, Long Neck, Rib Processing



SPEED FEED  
1364-1367

CARBIDE

WXL

2 FLUTE

30°




SHANK  
h6

STUB

PACKED  
1 PIECE

Cutting Diameter Tolerance	
0.2mm ≤ D ≤ 5mm	+0 / -0.015mm



EDP Number	Dia.	Length of Cut	Neck Length	Overall Length	Shank Dia.	
						D (mm)
3131201	●	0.20	0.30	0.50	45.00	4.00
3131202	●	0.20	0.30	1.00	45.00	4.00
3131203	●	0.20	0.30	1.50	45.00	4.00
3131204	●	0.20	0.30	2.00	45.00	4.00
3131205	●	0.20	0.30	2.50	45.00	4.00
3131206	●	0.20	0.30	3.00	45.00	4.00
3131207	●	0.20	0.30	3.50	45.00	4.00
3131208	●	0.20	0.30	4.00	45.00	4.00
3131302	●	0.30	0.45	1.00	45.00	4.00
3131303	●	0.30	0.45	1.50	45.00	4.00
3131304	●	0.30	0.45	2.00	45.00	4.00
3131305	●	0.30	0.45	2.50	45.00	4.00
3131306	●	0.30	0.45	3.00	45.00	4.00
3131308	●	0.30	0.45	4.00	45.00	4.00
3131310	●	0.30	0.45	5.00	45.00	4.00
3131312	●	0.30	0.45	6.00	45.00	4.00
3131318	●	0.30	0.45	9.00	45.00	4.00
3131403	●	0.40	0.60	1.50	45.00	4.00
3131404	●	0.40	0.60	2.00	45.00	4.00
3131406	●	0.40	0.60	3.00	45.00	4.00
3131408	●	0.40	0.60	4.00	45.00	4.00
3131410	●	0.40	0.60	5.00	45.00	4.00
3131412	●	0.40	0.60	6.00	45.00	4.00
3131414	●	0.40	0.60	7.00	45.00	4.00
3131416	●	0.40	0.60	8.00	45.00	4.00
3131418	●	0.40	0.60	9.00	45.00	4.00
3131420	●	0.40	0.60	10.00	45.00	4.00
3131424	●	0.40	0.60	12.00	45.00	4.00
3131501	●	0.50	0.70	1.50	45.00	4.00
3131502	●	0.50	0.70	2.00	45.00	4.00
3131503	●	0.50	0.70	3.00	45.00	4.00
3131504	●	0.50	0.70	4.00	45.00	4.00
3131505	●	0.50	0.70	5.00	45.00	4.00
3131506	●	0.50	0.70	6.00	45.00	4.00
3131507	●	0.50	0.70	7.00	45.00	4.00
3131508	●	0.50	0.70	8.00	45.00	4.00
3131509	●	0.50	0.70	9.00	45.00	4.00
3131510	●	0.50	0.70	10.00	45.00	4.00
3131512	●	0.50	0.70	12.00	45.00	4.00
3131515	●	0.50	0.70	15.00	50.00	4.00
3131602	●	0.60	0.90	2.00	45.00	4.00
3131603	●	0.60	0.90	3.00	45.00	4.00
3131604	●	0.60	0.90	4.00	45.00	4.00
3131605	●	0.60	0.90	5.00	45.00	4.00
3131606	●	0.60	0.90	6.00	45.00	4.00
3131607	●	0.60	0.90	7.00	45.00	4.00
3131608	●	0.60	0.90	8.00	45.00	4.00
3131610	●	0.60	0.90	10.00	45.00	4.00

EDP Number	Dia.	Length of Cut	Neck Length	Overall Length	Shank Dia.	
						D (mm)
3131612	●	0.60	0.90	12.00	45.00	4.00
3131615	●	0.60	0.90	15.00	50.00	4.00
3131618	●	0.60	0.90	18.00	50.00	4.00
3131702	●	0.70	1.00	2.00	45.00	4.00
3131704	●	0.70	1.00	4.00	45.00	4.00
3131706	●	0.70	1.00	6.00	45.00	4.00
3131708	●	0.70	1.00	8.00	45.00	4.00
3131710	●	0.70	1.00	10.00	45.00	4.00
3131804	●	0.80	1.20	4.00	45.00	4.00
3131806	●	0.80	1.20	6.00	45.00	4.00
3131808	●	0.80	1.20	8.00	45.00	4.00
3131810	●	0.80	1.20	10.00	45.00	4.00
3131812	●	0.80	1.20	12.00	45.00	4.00
3131814	●	0.80	1.20	14.00	50.00	4.00
3131816	●	0.80	1.20	16.00	50.00	4.00
3131820	●	0.80	1.20	20.00	55.00	4.00
3131824	●	0.80	1.20	24.00	60.00	4.00
3131904	●	0.90	1.35	4.00	45.00	4.00
3131906	●	0.90	1.35	6.00	45.00	4.00
3131908	●	0.90	1.35	8.00	45.00	4.00
3131910	●	0.90	1.35	10.00	45.00	4.00
3131915	●	0.90	1.35	15.00	50.00	4.00
3132003	●	1.00	1.50	3.00	45.00	4.00
3132004	●	1.00	1.50	4.00	45.00	4.00
3132005	●	1.00	1.50	5.00	45.00	4.00
3132006	●	1.00	1.50	6.00	45.00	4.00
3132007	●	1.00	1.50	7.00	45.00	4.00
3132008	●	1.00	1.50	8.00	45.00	4.00
3132009	●	1.00	1.50	9.00	45.00	4.00
3132010	●	1.00	1.50	10.00	45.00	4.00
3132012	●	1.00	1.50	12.00	45.00	4.00
3132014	●	1.00	1.50	14.00	50.00	4.00
3132016	●	1.00	1.50	16.00	50.00	4.00
3132018	●	1.00	1.50	18.00	55.00	4.00
3132020	●	1.00	1.50	20.00	55.00	4.00
3132022	●	1.00	1.50	22.00	60.00	4.00
3132025	●	1.00	1.50	25.00	60.00	4.00
3132030	●	1.00	1.50	30.00	70.00	4.00
3132204	●	1.20	1.80	4.00	45.00	4.00
3132206	●	1.20	1.80	6.00	45.00	4.00
3132208	●	1.20	1.80	8.00	45.00	4.00
3132210	●	1.20	1.80	10.00	45.00	4.00
3132212	●	1.20	1.80	12.00	45.00	4.00
3132214	●	1.20	1.80	14.00	50.00	4.00
3132216	●	1.20	1.80	16.00	50.00	4.00
3132220	●	1.20	1.80	20.00	55.00	4.00
3132406	●	1.40	2.10	6.00	45.00	4.00
3132408	●	1.40	2.10	8.00	45.00	4.00

● Stocked ○ Available Upon Request; MOQ May Apply  
▲ Globally Stocked



● Stocked ○ Available Upon Request; MOQ May Apply  
▲ Globally Stocked



CONTINUED ➔

P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel	300	400	17-4 PH		Aluminum		Nickel Alloy	Titanium	Hardened Steel			
Low	Medium	High							6061	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
1010	1035	1065	4140	4340				6061	7075							
○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

○ Good ○ Best





### List 3791 (Continued)


EXOCARB® WXL®-LN-EDS, Long Neck, Rib Processing



SPEED FEED  
1364-1367

CARBIDE	WXL	2 FLUTE	30°			SHANK h6	STUB	PACKED 1 PIECE
---------	-----	---------	-----	--	--	-------------	------	-------------------

Cutting Diameter Tolerance	
0.2mm ≤ D ≤ 5mm	+0 / -0.015mm



EDP Number	Dia.	Length of Cut	Neck Length	Overall Length	Shank Dia.	
						D (mm)
3132410	●	1.40	2.10	10.00	45.00	4.00
3132412	●	1.40	2.10	12.00	45.00	4.00
3132414	●	1.40	2.10	14.00	50.00	4.00
3132416	●	1.40	2.10	16.00	50.00	4.00
3132422	●	1.40	2.10	22.00	60.00	4.00
3132504	●	1.50	2.30	4.00	45.00	4.00
3132506	●	1.50	2.30	6.00	45.00	4.00
3132508	●	1.50	2.30	8.00	45.00	4.00
3132510	●	1.50	2.30	10.00	45.00	4.00
3132512	●	1.50	2.30	12.00	45.00	4.00
3132514	●	1.50	2.30	14.00	50.00	4.00
3132516	●	1.50	2.30	16.00	50.00	4.00
3132518	●	1.50	2.30	18.00	55.00	4.00
3132520	●	1.50	2.30	20.00	55.00	4.00
3132525	●	1.50	2.30	25.00	60.00	4.00
3132530	●	1.50	2.30	30.00	70.00	4.00
3132538	●	1.50	2.30	38.00	80.00	4.00
3132540	●	1.50	2.30	40.00	80.00	4.00
3132545	●	1.50	2.30	45.00	80.00	4.00
3132606	●	1.60	2.40	6.00	45.00	4.00
3132608	●	1.60	2.40	8.00	45.00	4.00
3132610	●	1.60	2.40	10.00	45.00	4.00
3132612	●	1.60	2.40	12.00	45.00	4.00
3132614	●	1.60	2.40	14.00	50.00	4.00
3132616	●	1.60	2.40	16.00	50.00	4.00
3132618	●	1.60	2.40	18.00	55.00	4.00
3132620	●	1.60	2.40	20.00	55.00	4.00
3132806	●	1.80	2.70	6.00	45.00	4.00
3132808	●	1.80	2.70	8.00	45.00	4.00
3132810	●	1.80	2.70	10.00	45.00	4.00
3132812	●	1.80	2.70	12.00	45.00	4.00
3132814	●	1.80	2.70	14.00	50.00	4.00
3132816	●	1.80	2.70	16.00	50.00	4.00
3132818	●	1.80	2.70	18.00	55.00	4.00
3132820	●	1.80	2.70	20.00	55.00	4.00
3132825	●	1.80	2.70	25.00	60.00	4.00
3133006	●	2.00	3.00	6.00	45.00	4.00
3133008	●	2.00	3.00	8.00	45.00	4.00
3133010	●	2.00	3.00	10.00	45.00	4.00
3133012	●	2.00	3.00	12.00	45.00	4.00
3133014	●	2.00	3.00	14.00	50.00	4.00
3133016	●	2.00	3.00	16.00	50.00	4.00
3133018	●	2.00	3.00	18.00	55.00	4.00
3133020	●	2.00	3.00	20.00	55.00	4.00
3133025	●	2.00	3.00	25.00	60.00	4.00
3133030	●	2.00	3.00	30.00	70.00	4.00

EDP Number	Dia.	Length of Cut	Neck Length	Overall Length	Shank Dia.	
						D (mm)
3133035	●	2.00	3.00	35.00	80.00	4.00
3133040	●	2.00	3.00	40.00	90.00	4.00
3133050	●	2.00	3.00	50.00	100.00	4.00
3133060	●	2.00	3.00	60.00	110.00	4.00
3133508	●	2.50	3.70	8.00	45.00	4.00
3133510	●	2.50	3.70	10.00	45.00	4.00
3133512	●	2.50	3.70	12.00	45.00	4.00
3133514	●	2.50	3.70	14.00	50.00	4.00
3133516	●	2.50	3.70	16.00	55.00	4.00
3133518	●	2.50	3.70	18.00	55.00	4.00
3133520	●	2.50	3.70	20.00	60.00	4.00
3133525	●	2.50	3.70	25.00	70.00	4.00
3133530	●	2.50	3.70	30.00	80.00	4.00
3133540	●	2.50	3.70	40.00	90.00	4.00
3133550	●	2.50	3.70	50.00	100.00	4.00
3134008	●	3.00	4.50	8.00	45.00	6.00
3134010	●	3.00	4.50	10.00	45.00	6.00
3134012	●	3.00	4.50	12.00	45.00	6.00
3134014	●	3.00	4.50	14.00	50.00	6.00
3134016	●	3.00	4.50	16.00	55.00	6.00
3134018	●	3.00	4.50	18.00	55.00	6.00
3134020	●	3.00	4.50	20.00	60.00	6.00
3134025	●	3.00	4.50	25.00	65.00	6.00
3134030	●	3.00	4.50	30.00	80.00	6.00
3134035	●	3.00	4.50	35.00	90.00	6.00
3134040	●	3.00	4.50	40.00	90.00	6.00
3134050	●	3.00	4.50	50.00	100.00	6.00
3135012	●	4.00	6.00	12.00	50.00	6.00
3135016	●	4.00	6.00	16.00	60.00	6.00
3135020	●	4.00	6.00	20.00	60.00	6.00
3135025	●	4.00	6.00	25.00	70.00	6.00
3135030	●	4.00	6.00	30.00	80.00	6.00
3135035	●	4.00	6.00	35.00	90.00	6.00
3135040	●	4.00	6.00	40.00	90.00	6.00
3135045	●	4.00	6.00	45.00	100.00	6.00
3135050	●	4.00	6.00	50.00	100.00	6.00
3135060	●	4.00	6.00	60.00	110.00	6.00
3136016	●	5.00	7.50	16.00	60.00	6.00
3136020	●	5.00	7.50	20.00	70.00	6.00
3136025	●	5.00	7.50	25.00	70.00	6.00
3136030	●	5.00	7.50	30.00	90.00	6.00
3136035	●	5.00	7.50	35.00	90.00	6.00
3136040	●	5.00	7.50	40.00	100.00	6.00
3136050	●	5.00	7.50	50.00	110.00	6.00
3136060	●	5.00	7.50	60.00	120.00	6.00

● Stocked ○ Available Upon Request; MOQ May Apply  
▲ Globally Stocked



● Stocked ○ Available Upon Request; MOQ May Apply  
▲ Globally Stocked



P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium				
Low	Medium	High			300	400	17-4 PH		6061 7075	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

○ Good ○ Best

