



List 3794

EXOCARB® WXL®-LN-EMS, Long Neck, Rib Processing



SPEED FEED
1370-1371

CARBIDE	WXL	4 FLUTE	35°	SHANK h6	STUB	PACKED 1 PIECE
---------	-----	---------	-----	----------	------	----------------

Cutting Diameter Tolerance	
1mm ≤ D ≤ 3mm	+0 / -0.015mm



EDP Number	Dia.	Length of Cut	Neck Length	Neck Dia.	Overall Length	Shank Dia.	
							D (mm)
3172004	●	1.00	1.50	4.00	0.95	45.00	4.00
3172006	●	1.00	1.50	6.00	0.95	45.00	4.00
3172008	●	1.00	1.50	8.00	0.95	45.00	4.00
3172010	●	1.00	1.50	10.00	0.95	45.00	4.00
3172012	●	1.00	1.50	12.00	0.95	45.00	4.00
3172016	●	1.00	1.50	16.00	0.95	50.00	4.00
3172206	●	1.20	1.80	6.00	1.15	45.00	4.00
3172208	●	1.20	1.80	8.00	1.15	45.00	4.00
3172210	●	1.20	1.80	10.00	1.15	45.00	4.00
3172212	●	1.20	1.80	12.00	1.15	45.00	4.00
3172216	●	1.20	1.80	16.00	1.15	50.00	4.00
3172406	●	1.40	2.10	6.00	1.35	45.00	4.00
3172408	●	1.40	2.10	8.00	1.35	45.00	4.00
3172410	●	1.40	2.10	10.00	1.35	45.00	4.00
3172412	●	1.40	2.10	12.00	1.35	45.00	4.00
3172414	●	1.40	2.10	14.00	1.35	50.00	4.00
3172416	●	1.40	2.10	16.00	1.35	50.00	4.00
3172422	●	1.40	2.10	22.00	1.35	60.00	4.00
3172506	●	1.50	2.30	6.00	1.45	45.00	4.00
3172508	●	1.50	2.30	8.00	1.45	45.00	4.00
3172510	●	1.50	2.30	10.00	1.45	45.00	4.00
3172512	●	1.50	2.30	12.00	1.45	45.00	4.00
3172514	●	1.50	2.30	14.00	1.45	50.00	4.00
3172516	●	1.50	2.30	16.00	1.45	50.00	4.00
3172518	●	1.50	2.30	18.00	1.45	55.00	4.00
3172520	●	1.50	2.30	20.00	1.45	55.00	4.00
3172606	●	1.60	2.40	6.00	1.55	45.00	4.00
3172608	●	1.60	2.40	8.00	1.55	45.00	4.00
3172610	●	1.60	2.40	10.00	1.55	45.00	4.00
3172612	●	1.60	2.40	12.00	1.55	45.00	4.00
3172614	●	1.60	2.40	14.00	1.55	50.00	4.00
3172616	●	1.60	2.40	16.00	1.55	50.00	4.00
3172618	●	1.60	2.40	18.00	1.55	55.00	4.00

EDP Number	Dia.	Length of Cut	Neck Length	Neck Dia.	Overall Length	Shank Dia.	
							D (mm)
3172620	●	1.60	2.40	20.00	1.55	55.00	4.00
3172625	●	1.60	2.40	25.00	1.55	60.00	4.00
3172806	●	1.80	2.70	6.00	1.75	45.00	4.00
3172808	●	1.80	2.70	8.00	1.75	45.00	4.00
3172810	●	1.80	2.70	10.00	1.75	45.00	4.00
3172812	●	1.80	2.70	12.00	1.75	45.00	4.00
3172814	●	1.80	2.70	14.00	1.75	50.00	4.00
3172816	●	1.80	2.70	16.00	1.75	50.00	4.00
3172818	●	1.80	2.70	18.00	1.75	55.00	4.00
3172820	●	1.80	2.70	20.00	1.75	55.00	4.00
3172825	●	1.80	2.70	25.00	1.75	60.00	4.00
3173006	●	2.00	3.00	6.00	1.95	45.00	4.00
3173008	●	2.00	3.00	8.00	1.95	45.00	4.00
3173010	●	2.00	3.00	10.00	1.95	45.00	4.00
3173012	●	2.00	3.00	12.00	1.95	45.00	4.00
3173014	●	2.00	3.00	14.00	1.95	50.00	4.00
3173016	●	2.00	3.00	16.00	1.95	50.00	4.00
3173018	●	2.00	3.00	18.00	1.95	55.00	4.00
3173020	●	2.00	3.00	20.00	1.95	55.00	4.00
3173025	●	2.00	3.00	25.00	1.95	60.00	4.00
3173030	●	2.00	3.00	30.00	1.95	70.00	4.00
3173508	●	2.50	3.70	8.00	2.40	45.00	4.00
3173512	●	2.50	3.70	12.00	2.40	45.00	4.00
3173516	●	2.50	3.70	16.00	2.40	55.00	4.00
3173520	●	2.50	3.70	20.00	2.40	60.00	4.00
3173525	●	2.50	3.70	25.00	2.40	70.00	4.00
3174008	●	3.00	4.50	8.00	2.85	45.00	6.00
3174012	●	3.00	4.50	12.00	2.85	45.00	6.00
3174016	●	3.00	4.50	16.00	2.85	55.00	6.00
3174020	●	3.00	4.50	20.00	2.85	60.00	6.00
3174025	●	3.00	4.50	25.00	2.85	65.00	6.00
3174030	●	3.00	4.50	30.00	2.85	80.00	6.00

● Stocked ○ Available Upon Request; MOQ May Apply
▲ Globally Stocked



● Stocked ○ Available Upon Request; MOQ May Apply
▲ Globally Stocked



P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel	300	400	17-4 PH		Aluminum		Nickel Alloy	Titanium	Hardened Steel			
Low	Medium	High							6061	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
1010	1035	1065	4140	4340				6061	7075	6061	7075	Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	

○ Good ○ Best



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX