



List 440

OSG COBALT HSS EX-REB

SPEED FEED 150S	HSS-Co	BR	ROUGH	30°			WELDON FLAT	STUB	REG	LONG	PACKED 1 PIECE
--------------------	--------	----	-------	-----	--	--	-------------	------	-----	------	-------------------



EDP Number		Diameter		Length of Cut	Overall Length	Shank Diameter	Number of Flutes
		D (Fractional Size)	Lc (Inch)	L (Inch)	d (Inch)		
4400100	●	1/2	1.250	3.250	0.500	4	
4400300	●	1/2	2.000	4.000	0.500	4	
4400500	●	5/8	1.625	3.750	0.625	4	
4400700	●	5/8	2.500	4.625	0.625	4	
4401300	●	3/4	1.625	3.875	0.750	4	
4401500	●	3/4	3.000	5.250	0.750	4	
4410500	●	1	2.000	4.500	1.000	4	
4410900	●	1	4.000	6.500	1.000	4	
4412100	●	1-1/4	2.000	4.500	1.250	6	
4412500	●	1-1/4	4.000	6.500	1.250	6	
4413300	●	1-1/2	2.000	4.500	1.250	6	
4413700	●	1-1/2	4.000	6.500	1.250	6	
4420900	●	2	4.000	7.750	2.000	8	
4421100	●	2	6.000	9.750	2.000	8	

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked

Note: Other coatings available upon request. 2" diameter shanks have combination drive.



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

P					M			K	N		S		H						
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel						
Carbon Steel			Alloy Steel	Die Steel	Aluminum		Nickel Alloy		Titanium										
Low	Medium	High			6061	7075				Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC			
1010	1035	1065	4140	4340	300	400	17-4 PH												
○	○	○	○	○	○	○	○	○	○	○		○	○						

○ Good ⊗ Best

