



List 4670

EXOCARB® AM-CRE



SPEED FEED
1446

CARBIDE

DUROREY

60°



SHANK
h4

STUB

PACKED
1 PIECE


Cutting Diameter Tolerance	
1/4" ≤ D ≤ 1/2"	+/- 0.0004"



6 Flute



8 Flute



EDP Number	Diameter	Corner Radius	Length of Cut	Overall Length	Shank Diameter	Number of Flutes
46700023	1/4	0.031	0.375	3.000	0.250	6
46700123	1/4	0.063	0.375	3.000	0.250	6
46700223	5/16	0.047	0.469	3.000	0.313	6
46700323	5/16	0.094	0.469	3.500	0.313	6
46700423	3/8	0.047	0.563	3.500	0.375	6
46700523	3/8	0.094	0.563	3.500	0.375	6
46700623	1/2	0.063	0.750	4.000	0.500	8
46700723	1/2	0.125	0.750	4.000	0.500	8

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H						
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel						
Carbon Steel			Alloy Steel	Die Steel	Aluminum		Nickel Alloy		Titanium										
Low	Medium	High			6061	7075				Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC			
1010	1035	1045	1065	4140	4340	300	400	17-4 PH											
						○	○	○				○	○			○	○		○

○ Good ○ Best

