




List 52504

OSG PHOENIX® P4D, Flat Shank



EDP Number	Designation	Diameter	Drilling Depth	Overall Length	Shank Diameter	Shank Length	Applicable Insert
		D (in)	l1 (in)	L (in)	d (in)	l2 (in)	
52504063	P4D0484FS075A03	0.484	1.938	4.418	0.750	1.969	XCMT03
52504064	P4D0500FS075A03	0.500	2.000	4.480	0.750	1.969	XCMT03
52504065	P4D0516FS075A03	0.516	2.063	4.543	0.750	1.969	XCMT03
52504066	P4D0531FS075A03	0.531	2.125	4.605	0.750	1.969	XCMT03
52504067	P4D0547FS075A03	0.547	2.188	4.668	0.750	1.969	XCMT03
52504068	P4D0563FS075A03	0.563	2.250	4.730	0.750	1.969	XCMT03
52504069	P4D0578FS075A03	0.578	2.313	4.793	0.750	1.969	XCMT03
52504026	P4D0594FS075A04	0.594	2.375	4.935	0.750	1.969	XCMT04
52504027	P4D0609FS075A04	0.609	2.438	4.995	0.750	1.969	XCMT04
52504008	P4D0625FS075A04	0.625	2.500	5.059	0.750	1.969	XCMT04
52504028	P4D0641FS075A04	0.641	2.563	5.123	0.750	1.969	XCMT04
52504009	P4D0656FS075A04	0.656	2.625	5.183	0.750	1.969	XCMT04
52504029	P4D0672FS075A05	0.672	2.688	5.365	0.750	1.969	XCMT05
52504010	P4D0688FS075A05	0.688	2.750	5.429	0.750	1.969	XCMT05
52504030	P4D0703FS075A05	0.703	2.813	5.489	0.750	1.969	XCMT05
52504031	P4D0719FS100A05	0.719	2.875	5.789	1.000	2.205	XCMT05
52504032	P4D0734FS100A05	0.734	2.938	5.849	1.000	2.205	XCMT05
52504011	P4D0750FS100A06	0.750	3.000	5.913	1.000	2.205	XCMT06
52504033	P4D0766FS100A06	0.766	3.063	5.978	1.000	2.205	XCMT06
52504034	P4D0781FS100A06	0.781	3.125	6.037	1.000	2.205	XCMT06
52504035	P4D0797FS100A06	0.797	3.188	6.102	1.000	2.205	XCMT06
52504012	P4D0812FS100A06	0.813	3.250	6.161	1.000	2.205	XCMT06
52504036	P4D0828FS100A07	0.828	3.313	6.422	1.000	2.205	XCMT07
52504037	P4D0844FS100A07	0.844	3.375	6.486	1.000	2.205	XCMT07
52504038	P4D0859FS100A07	0.859	3.438	6.546	1.000	2.205	XCMT07
52504000	P4D0875FS100A07	0.875	3.500	6.610	1.000	2.205	XCMT07
52504039	P4D0891FS100A07	0.891	3.563	6.674	1.000	2.205	XCMT07
52504040	P4D0906FS100A07	0.906	3.625	6.734	1.000	2.205	XCMT07
52504041	P4D0922FS100A07	0.922	3.688	6.798	1.000	2.205	XCMT07
52504001	P4D0937FS125A07	0.938	3.750	7.016	1.250	2.362	XCMT07
52504042	P4D0953FS125A07	0.953	3.813	7.080	1.250	2.362	XCMT07
52504043	P4D0969FS125A07	0.969	3.875	7.144	1.250	2.362	XCMT07
52504044	P4D0984FS125A08	0.984	3.938	7.204	1.250	2.362	XCMT08
52504002	P4D1000FS125A08	1.000	4.000	7.268	1.250	2.362	XCMT08
52504045	P4D1031FS125A08	1.031	4.125	7.392	1.250	2.362	XCMT08
52504003	P4D1062FS125A08	1.063	4.250	7.516	1.250	2.362	XCMT08
52504046	P4D1094FS125A08	1.094	4.375	7.644	1.250	2.362	XCMT08
52504004	P4D1125FS125A08	1.125	4.500	7.768	1.250	2.362	XCMT08
52504047	P4D1156FS125A09	1.156	4.625	7.892	1.250	2.362	XCMT09
52504005	P4D1187FS125A09	1.188	4.750	8.016	1.250	2.362	XCMT09
52504048	P4D1219FS125A09	1.219	4.875	8.144	1.250	2.362	XCMT09
52504006	P4D1250FS125A09	1.250	5.000	8.268	1.250	2.362	XCMT09
52504049	P4D1281FS150A09	1.281	5.125	8.785	1.500	2.756	XCMT09
52504007	P4D1312FS150A09	1.313	5.250	8.909	1.500	2.756	XCMT09
52504050	P4D1344FS150A10	1.344	5.375	9.037	1.500	2.756	XCMT10
52504013	P4D1375FS150A10	1.375	5.500	9.161	1.500	2.756	XCMT10
52504051	P4D1406FS150A10	1.406	5.625	9.285	1.500	2.756	XCMT10
52504014	P4D1437FS150A10	1.438	5.750	9.409	1.500	2.756	XCMT10
52504052	P4D1469FS150A10	1.469	5.875	9.537	1.500	2.756	XCMT10
52504015	P4D1500FS150A10	1.500	6.000	9.661	1.500	2.756	XCMT10
52504053	P4D1531FS150A10	1.531	6.125	9.785	1.500	2.756	XCMT10
52504016	P4D1563FS150A12	1.563	6.250	10.189	1.500	2.756	XCMT12
52504054	P4D1594FS150A12	1.594	6.375	10.313	1.500	2.756	XCMT12

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked






List 52504 (Continued)

OSG PHOENIX® P4D, Flat Shank

363	282-283	284	STEEL	2 FLUTE	1 PIECE



EDP Number		Designation	Diameter	Drilling Depth	Overall Length	Shank Diameter	Shank Length	Applicable Insert
			D (in)	L1 (in)	L (in)	d (in)	L2 (in)	
52504017	●	P4D1625FS150A12	1.625	6.500	10.437	1.500	2.756	XCMT12
52504055	●	P4D1656FS150A12	1.656	6.625	10.561	1.500	2.756	XCMT12
52504018	●	P4D1688FS150A12	1.688	6.750	10.689	1.500	2.756	XCMT12
52504056	●	P4D1719FS150A12	1.719	6.875	10.813	1.500	2.756	XCMT12
52504019	●	P4D1750FS150A12	1.750	7.000	10.937	1.500	2.756	XCMT12
52504057	●	P4D1781FS150A13	1.781	7.125	11.061	1.500	2.756	XCMT13
52504058	●	P4D1813FS150A13	1.813	7.250	11.189	1.500	2.756	XCMT13
52504059	●	P4D1844FS150A13	1.844	7.375	11.313	1.500	2.756	XCMT13
52504020	●	P4D1875FS150A13	1.875	7.500	11.437	1.500	2.756	XCMT13
52504060	●	P4D1906FS150A13	1.906	7.625	11.561	1.500	2.756	XCMT13
52504061	●	P4D1938FS150A13	1.938	7.750	11.689	1.500	2.756	XCMT13
52504062	●	P4D1969FS150A14	1.969	7.875	11.813	1.500	2.756	XCMT14
52504021	●	P4D2000FS150A14	2.000	8.000	11.937	1.500	2.756	XCMT14
52504022	●	P4D2125FS150A14	2.125	8.500	12.437	1.500	2.756	XCMT14
52504023	●	P4D2250FS150A16	2.250	9.000	12.937	1.500	2.756	XCMT16
52504024	●	P4D2375FS150A16	2.375	9.500	13.437	1.500	2.756	XCMT16
52504025	●	P4D2500FS150A16	2.500	10.000	13.937	1.500	2.756	XCMT16

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



DESIGNATION EXPLANATION

P4D-0484-FS-075-A-03



See Full Detail on Page 360

P	M	K	N	S	H
Steel	Stainless Steel	Cast Iron	Non-Ferrous	HRSA	Hardened Steel
○	○	○	○	○	○

Material recommendation based on inserts compatible with this tool body.

○ Good ○ Best

