




List 52513

OSG PHOENIX® PDZ-2D, Flat Shank

NEW



SPEED FEED 368	INSERTS 292	ACCS. 293	STEEL			PACKED 1 PIECE
--------------------------	-----------------------	---------------------	--------------	--	--	--------------------------



EDP Number	Designation	Diameter		Drilling Depth		Overall Length		Shank Diameter		Shank Length		Applicable Insert
		D (in)	I1 (in)	L (in)	d (in)	I2 (in)	d (in)	I2 (in)				
52513002	● PDZ0688FS075A05-2D	0.688	1.375	4.053	0.750	1.969	ZPNT05					
52513003	● PDZ0750FS100A06-2D	0.750	1.500	4.413	1.000	2.205	ZPNT06					
52513004	● PDZ0812FS100A06-2D	0.813	1.625	4.537	1.000	2.205	ZPNT06					
52513005	● PDZ0875FS100A06-2D	0.875	1.750	4.860	1.000	2.205	ZPNT06					
52513006	● PDZ0937FS125A07-2D	0.938	1.875	5.142	1.250	2.362	ZPNT07					
52513007	● PDZ1000FS125A07-2D	1.000	2.000	5.268	1.250	2.362	ZPNT07					
52513008	● PDZ1062FS125A08-2D	1.063	2.125	5.392	1.250	2.362	ZPNT08					
52513009	● PDZ1125FS125A08-2D	1.125	2.250	5.518	1.250	2.362	ZPNT08					
52513010	● PDZ1187FS125A08-2D	1.188	2.375	5.642	1.250	2.362	ZPNT08					
52513011	● PDZ1250FS125A09-2D	1.250	2.500	5.768	1.250	2.362	ZPNT09					
52513012	● PDZ1312FS150A09-2D	1.313	2.625	6.285	1.500	2.756	ZPNT09					
52513013	● PDZ1375FS150A09-2D	1.375	2.750	6.411	1.500	2.756	ZPNT09					
52513014	● PDZ1437FS150A10-2D	1.438	2.875	6.535	1.500	2.756	ZPNT10					
52513015	● PDZ1500FS150A10-2D	1.500	3.000	6.661	1.500	2.756	ZPNT10					

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



DESIGNATION EXPLANATION

PDZ-0688-FS-075-A-05-2D



See Full Detail on Page 360

P	M	K	N	S	H
Steel	Stainless Steel	Cast Iron	Non-Ferrous	HRSA	Hardened Steel
◎	◎	◎	○	○	○

Material recommendation based on inserts compatible with this tool body.

○ Good ◎ Best

