




List 52606

OSG PHOENIX[®] PMD ASF, Screw Fit Head



SPEED FEED 1532-1533	INSERTS 1233-1236	ACCS. 1237	STEEL	2 FLUTE	PACKED 1 PIECE
--------------------------------	-----------------------------	----------------------	--------------	----------------	--------------------------



EDP Number	Designation	Dia.	Number of Effective Flutes	Pilot Dia.	Thread Size	Flange Dia.	Length of Cut	Drilling Depth	Overall Length	Spanner Wrench	Center Insert	Peripheral Insert
		D (Inch)		Da (Inch)	Dg (mm)	D2 (Inch)	Lc (Inch)	l1 (Inch)	L (Inch)			
52606001	▲ PMD11R100ASF12-1	1.000	1	0.492	M12	0.905	0.394	1.000	1.890	17	ZPNT13	ZDKT11
52606002	▲ PMD11R125ASF16-1	1.250	1	0.669	M16	1.102	0.394	1.250	2.087	22	ZPNT17	ZDKT11

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



ABOUT OSG

DRILLING

THREADING


MILLING

HOLDERS

INDEX

DESIGNATION EXPLANATION

PMD 11 R 100 ASF 12-1



See Full Detail on Page 1524

P	M	K	N	S	H
Steel	Stainless Steel	Cast Iron	Non-Ferrous	HRSA	Hardened Steel
○	⊙	⊙	⊙	⊙	⊙

Material recommendation based on inserts compatible with this tool body.

○ Good ⊙ Best

