



List 5315

EXOCARB® MAX-MINI UVM-LDS, Miniature, Pilot

SPEED FEED	CARBIDE	SS	2 FLUTE	30°	SHANK	PACKED
331					h3	1 PIECE

Cutting Diameter Tolerance		
Size (mm)	mm	inch
0.05	+0/-0.003	+0/-0.0001



EDP Number		Diameter (D)					Flute Length FL (mm)	Overall Length L (mm)	Shank Diameter	
		Fractional Size	Wire Gage	Letter Size	mm	Inch			d (in)	d (mm)
8589205	●	-	-	-	0.050	0.00197	0.08	38.00	-	3.00
8589255	●	-	-	-	0.050	0.00197	0.08	38.00	0.125	-

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

P					M			K	N		S		H					
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel					
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium						
Low	Medium	High			300	400	17-4 PH		6061	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC
1010	1035	1065	4140	4340	○	○	○	○	○	○	○	○	○	○	○	○	○	○
1018	1045				○	○	○	○	○	○	○	○	○	○	○	○	○	○

○ Good ○ Best

