



EXOCARB® MAX-MINI



High Performance Micro Carbide Drills

List 5340

EXOCARB® MAX-MINI MRS-GDL, Precision Drill

SPEED FEED 333	CARBIDE	SS	2 FLUTE	TAPER	30°	SHANK h6	PACKED 1 PIECE
-------------------	---------	----	---------	-------	-----	-------------	-------------------

Cutting Diameter Tolerance		
Size (mm)	mm	inch
0.5 ≤ D ≤ 3	+0 / -0.008	+0 / -0.0003



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

EDP Number		Diameter (D)					Flute Length	Overall Length	Shank Diameter
		Fractional Size	Wire Gage	Letter Size	mm	Inch	FL (mm)	L (mm)	d (mm)
8577050	●	-	-	-	0.500	0.01969	6.00	42.00	3.00
8577054	●	-	-	-	0.540	0.02126	6.60	42.00	3.00
8577055	●	-	-	-	0.550	0.02165	6.60	42.00	3.00
8577056	●	-	-	-	0.560	0.02205	7.20	42.00	3.00
8577060	●	-	-	-	0.600	0.02362	7.20	42.00	3.00
8577063	●	-	-	-	0.630	0.02480	7.80	46.00	3.00
8577064	●	-	-	-	0.640	0.02520	7.80	46.00	3.00
8577065	●	-	-	-	0.650	0.02559	7.80	46.00	3.00
8577070	●	-	-	-	0.700	0.02756	8.40	46.00	3.00
8577071	●	-	-	-	0.710	0.02795	9.00	46.00	3.00
8577072	●	-	-	-	0.720	0.02835	9.00	46.00	3.00
8577073	●	-	-	-	0.730	0.02874	9.00	46.00	3.00
8577074	●	-	-	-	0.740	0.02913	9.00	46.00	3.00
8577075	●	-	-	-	0.750	0.02953	9.00	46.00	3.00
8577080	●	-	-	-	0.800	0.03150	9.60	46.00	3.00
8577081	●	-	-	-	0.810	0.03189	10.20	46.00	3.00
8577082	●	-	-	-	0.820	0.03228	10.20	46.00	3.00
8577090	●	-	-	-	0.900	0.03543	10.80	46.00	3.00
8577091	●	-	-	-	0.910	0.03583	11.40	46.00	3.00
8577092	●	-	-	-	0.920	0.03622	11.40	46.00	3.00
8577100	●	-	-	-	1.000	0.03937	12.00	46.00	3.00
8577110	●	-	-	-	1.100	0.04331	13.20	50.00	3.00
8577111	●	-	-	-	1.110	0.04370	13.80	50.00	3.00
8577112	●	-	-	-	1.120	0.04409	13.80	50.00	3.00
8577115	●	-	-	-	1.150	0.04528	13.80	50.00	3.00
8577120	●	-	-	-	1.200	0.04724	14.40	50.00	3.00
8577127	●	-	-	-	1.270	0.05000	15.60	50.00	3.00
8577128	●	-	-	-	1.280	0.05039	15.60	50.00	3.00
8577129	●	-	-	-	1.290	0.05079	15.60	50.00	3.00
8577130	●	-	-	-	1.300	0.05118	15.60	50.00	3.00
8577140	●	-	-	-	1.400	0.05512	16.80	54.00	3.00
8577145	●	-	-	-	1.450	0.05709	17.40	54.00	3.00
8577146	●	-	-	-	1.460	0.05748	18.00	54.00	3.00
8577147	●	-	-	-	1.470	0.05787	18.00	54.00	3.00
8577150	●	-	-	-	1.500	0.05906	18.00	54.00	3.00
8577151	●	-	-	-	1.510	0.05945	18.60	54.00	3.00
8577152	●	-	-	-	1.520	0.05984	18.60	54.00	3.00
8577153	●	-	-	-	1.530	0.06024	18.60	54.00	3.00
8577155	●	-	-	-	1.550	0.06102	18.60	54.00	3.00
8577156	●	-	-	-	1.560	0.06142	19.20	54.00	3.00
8577157	●	-	-	-	1.570	0.06181	19.20	54.00	3.00
8577160	●	-	-	-	1.600	0.06299	19.20	54.00	3.00
8577170	●	-	-	-	1.700	0.06693	20.40	58.00	3.00
8577180	●	-	-	-	1.800	0.07087	21.60	58.00	3.00
8577181	●	-	-	-	1.810	0.07126	22.20	58.00	3.00
8577182	●	-	-	-	1.820	0.07165	22.20	58.00	3.00
8577183	●	-	-	-	1.830	0.07205	22.20	58.00	3.00
8577190	●	-	-	-	1.900	0.07480	22.80	58.00	3.00
8577198	●	-	-	-	1.980	0.07795	24.00	58.00	3.00
8577199	●	-	-	-	1.990	0.07835	24.00	58.00	3.00
8577200	●	-	-	-	2.000	0.07874	24.00	58.00	3.00
8577210	●	-	-	-	2.100	0.08268	25.20	62.00	3.00

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked





List 5340 (Continued)

EXOCARB® MAX-MINI MRS-GDL, Precision Drill

SPEED FEED 333	CARBIDE	SS	2 FLUTE	TAPER	30°	SHANK h6	PACKED 1 PIECE
--------------------------	----------------	-----------	----------------	--------------	------------	--------------------	--------------------------

EDP Number		Diameter (D)					Flute Length FL (mm)	Overall Length L (mm)	Shank Diameter d (mm)
		Fractional Size	Wire Gage	Letter Size	mm	Inch			
8577212	●	-	-	-	2.120	0.08346	25.80	62.00	3.00
8577213	●	-	-	-	2.130	0.08386	25.80	62.00	3.00
8577214	●	-	-	-	2.140	0.08425	25.80	62.00	3.00
8577220	●	-	-	-	2.200	0.08661	26.40	62.00	3.00
8577229	●	-	-	-	2.290	0.09016	27.60	62.00	3.00
8577230	●	-	-	-	2.300	0.09055	27.60	62.00	3.00
8577231	●	-	-	-	2.310	0.09094	28.20	62.00	3.00
8577239	●	-	-	-	2.390	0.09409	28.80	62.00	3.00
8577240	●	-	-	-	2.400	0.09449	28.80	62.00	3.00
8577241	●	-	-	-	2.410	0.09488	29.40	66.00	3.00
8577242	●	-	-	-	2.420	0.09528	29.40	66.00	3.00
8577250	●	-	-	-	2.500	0.09843	30.00	66.00	3.00
8577255	●	-	-	-	2.550	0.10039	30.60	66.00	3.00
8577256	●	-	-	-	2.560	0.10079	31.20	66.00	3.00
8577257	●	-	-	-	2.570	0.10118	31.20	66.00	3.00
8577260	●	-	-	-	2.600	0.10236	31.20	66.00	3.00
8577270	●	-	-	-	2.700	0.10630	32.40	66.00	3.00
8577277	●	-	-	-	2.770	0.10906	33.60	66.00	3.00
8577278	●	-	-	-	2.780	0.10945	33.60	66.00	3.00
8577279	●	-	-	-	2.790	0.10984	33.60	66.00	3.00
8577280	●	-	-	-	2.800	0.11024	33.60	66.00	3.00
8577290	●	-	-	-	2.900	0.11417	34.80	66.00	3.00
8577300	●	-	-	-	3.000	0.11811	36.00	66.00	3.00

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked



P					M			K	N		S		H				
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel				
Carbon Steel			Alloy Steel	Die Steel	Aluminum		Nickel Alloy		Titanium								
Low	Medium	High			6061	7075				Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC	
○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

○ Good ○ Best

