




List 544

OSG COBALT HSS EBM

SPEED FEED 1504	HSS-Co	BR	4 FLUTE	30°			WELDED FLAT	STUB	REG	LONG	PACKED 1 PIECE
---------------------------	---------------	-----------	----------------	------------	--	--	--------------------	-------------	------------	-------------	--------------------------

Cutting Diameter Tolerance	
3/8" ≤ D ≤ 1-1/2"	+0.0011 / -0"



EDP Number		Diameter		Length of Cut	Overall Length	Shank Diameter
		D (Fractional Size)	Lc (Inch)	L (Inch)	d (Inch)	
5440500	●	3/8	0.750	2.500	0.375	
5449700	●	7/16	1.250	3.250	0.500	
5441100	●	1/2	1.250	3.250	0.500	
5442100	●	5/8	1.625	3.750	0.625	
5442200	●	5/8	2.500	4.625	0.625	
5443100	●	3/4	1.625	3.875	0.750	
5444100	●	7/8	1.875	4.125	0.875	
5445100	●	1	2.000	4.500	1.000	
5446100	●	1-1/4	2.000	4.500	1.250	
5446200	●	1-1/2	2.000	4.500	1.250	

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked
 Note: Other coatings available upon request.



P					M			K	N		S		H						
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel						
Carbon Steel			Alloy Steel	Die Steel	Aluminum		Nickel Alloy		Titanium										
Low	Medium	High			6061	7075				Casting	Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC			
1010	1035	1045	1065	4140	4340														
○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○

○ Good ○ Best

