

List 574

HY-PRO V CC-EMS

SPEED FEED 1414-1415	HSSE	BR	TiCN	30°			WELDON FLAT	STUB	REG	PACKED 1 PIECE
--------------------------------	-------------	-----------	-------------	------------	--	--	--------------------	-------------	------------	--------------------------

Cutting Diameter Tolerance	
1/8" ≤ D ≤ 1"	+0/-0.0011"



EDP Number	●	Diameter	Length of Cut	Overall Length	Shank Diameter	Number of Flutes	Surface Treatment
		D (Fractional Size)	Lc (Inch)	L (Inch)	d (Inch)		
5740100	●	1/8	0.375	2.313	0.375	4	BRIGHT
5740108	●	1/8	0.375	2.313	0.375	4	TiCN
5740200	●	5/32	0.438	2.375	0.375	4	BRIGHT
5740208	●	5/32	0.438	2.375	0.375	4	TiCN
5740300	●	3/16	0.500	2.375	0.375	4	BRIGHT
5740308	●	3/16	0.500	2.375	0.375	4	TiCN
5740400	●	7/32	0.563	2.438	0.375	4	BRIGHT
5740408	●	7/32	0.563	2.438	0.375	4	TiCN
5740500	●	1/4	0.625	2.438	0.375	4	BRIGHT
5740508	●	1/4	0.625	2.438	0.375	4	TiCN
5740600	●	9/32	0.688	2.500	0.375	4	BRIGHT
5740608	●	9/32	0.688	2.500	0.375	4	TiCN
5740700	●	5/16	0.750	2.500	0.375	4	BRIGHT
5740708	●	5/16	0.750	2.500	0.375	4	TiCN
5740800	●	11/32	0.750	2.500	0.375	4	BRIGHT
5740808	●	11/32	0.750	2.500	0.375	4	TiCN
5740900	●	3/8	0.750	2.500	0.375	4	BRIGHT
5740908	●	3/8	0.750	2.500	0.375	4	TiCN
5741000	●	13/32	1.000	2.688	0.375	4	BRIGHT
5741008	●	13/32	1.000	2.688	0.375	4	TiCN
5741100	●	7/16	1.000	2.688	0.375	4	BRIGHT
5741108	●	7/16	1.000	2.688	0.375	4	TiCN
5741200	●	15/32	1.250	3.250	0.500	4	BRIGHT
5741208	●	15/32	1.250	3.250	0.500	4	TiCN
5741400	●	1/2	1.250	3.250	0.500	4	BRIGHT
5741408	●	1/2	1.250	3.250	0.500	4	TiCN
5741500	●	17/32	1.375	3.375	0.500	4	BRIGHT
5741508	●	17/32	1.375	3.375	0.500	4	TiCN
5741600	●	9/16	1.375	3.375	0.500	4	BRIGHT
5741608	●	9/16	1.375	3.375	0.500	4	TiCN
5741700	●	19/32	1.375	3.375	0.500	4	BRIGHT
5741708	●	19/32	1.375	3.375	0.500	4	TiCN
5742300	●	5/8	1.625	3.750	0.625	4	BRIGHT
5742308	●	5/8	1.625	3.750	0.625	4	TiCN
5741900	●	21/32	1.625	3.625	0.500	4	BRIGHT
5741908	●	21/32	1.625	3.625	0.500	4	TiCN
5742000	●	11/16	1.625	3.625	0.500	4	BRIGHT
5742008	●	11/16	1.625	3.625	0.500	4	TiCN
5742400	●	11/16	1.625	3.750	0.625	4	BRIGHT
5742408	●	11/16	1.625	3.750	0.625	4	TiCN
5742100	●	23/32	1.625	3.625	0.500	4	BRIGHT
5742108	●	23/32	1.625	3.625	0.500	4	TiCN

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked
Note: Other coatings available upon request.

STE

CONTINUED

P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel	300	400	17-4 PH		Aluminum		Nickel Alloy	Titanium				
Low	Medium	High							6061	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
1010	1035	1045	1065	4140				4340	7075							
○	○	○	○	○	○	○		○	○	○		○	○	○	○	

○ Good ○ Best



