


List 597

OSG COBALT HSS TPET, 10° Taper per Side

SPEED FEED 1514	HSS-Co	BR	3 FLUTE	25°			WELDON FLAT	REG	LONG	EXTRA LONG	PACKED 1 PIECE
Cutting Diameter Tolerance											
3/32" ≤ D ≤ 1/4" +0 / -10'											



EDP Number		Diameter	Length of Cut	Overall Length	Shank Diameter
		D (Fractional Size)	Lc (Inch)	L (Inch)	d (Inch)
5972400	●	3/32	1.500	3.625	0.625
5974200	●	1/8	0.750	2.750	0.500
5974500	●	1/8	1.250	3.375	0.625
5976100	●	1/4	0.750	2.750	0.500
5976300	●	1/4	1.250	3.375	0.625
5976400	●	1/4	2.250	4.500	0.750

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked
 Note: Other coatings available upon request.



ABOUT OSG

DRILLING

THREADING

MILLING

HOLDERS

INDEX

P					M			K	N		S		H			
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel			
Carbon Steel			Alloy Steel	Die Steel	300	400	17-4 PH		Aluminum		Nickel Alloy	Titanium	Hardened Steel			
Low	Medium	High							6061	Casting			Inconel	6Al4V (30 HRC)	~35 HRC	35-45 HRC
1010	1035	1065	4140	4340	6061	7075										
○	○	○	⊗	⊗	○	○	○	○	○	○		○	○	○		

○ Good ⊗ Best

