




List 706

OSG CARBIDE COUNTERSINK

CARBIDE	BR	6 FLUTE	0°	PACKED 1 PIECE
---------	----	---------	----	-------------------



EDP Number		Diameter		Overall Length	Shank Diameter	Point Angle
		D (in)	D (in)	L (in)	d (in)	α
706-2500-060	●	1/4	0.25000	2.000	0.250	60
706-2500-082	●	1/4	0.25000	2.000	0.250	82
706-2500-090	●	1/4	0.25000	2.000	0.250	90
706-3750-060	●	3/8	0.37500	2.500	0.250	60
706-3750-082	●	3/8	0.37500	2.375	0.250	82
706-3750-090	●	3/8	0.37500	2.375	0.250	90
706-5000-060	●	1/2	0.50000	2.625	0.250	60
706-5000-082	●	1/2	0.50000	2.500	0.250	82
706-5000-090	●	1/2	0.50000	2.500	0.250	90
706-6250-060	●	5/8	0.62500	3.000	0.375	60
706-6250-082	●	5/8	0.62500	2.875	0.375	82
706-6250-090	●	5/8	0.62500	2.875	0.375	90
706-7500-060	●	3/4	0.75000	3.000	0.375	60
706-7500-082	●	3/4	0.75000	2.875	0.375	82
706-7500-090	●	3/4	0.75000	2.875	0.375	90
706-1000-060	●	1	1.00000	3.250	0.500	60
706-1000-082	●	1	1.00000	3.000	0.500	82
706-1000-090	●	1	1.00000	3.000	0.500	90

● Stocked ○ Available Upon Request; MOQ May Apply ▲ Globally Stocked
 Note: D ≥ 3/8 With brazed steel shank.



P					M			K	N		S		H					
Steel					Stainless Steel			Cast Iron	Non-Ferrous		HRSA		Hardened Steel					
Carbon Steel			Alloy Steel	Die Steel					Aluminum		Nickel Alloy	Titanium						
Low	Medium	High			300	400	17-4 PH	6061 7075	Casting	Inconel			6Al4V (30 HRC)	~35 HRC	35-45 HRC	45-50 HRC	50-70 HRC	
1010	1035	1065	4140	4340														
1018	1045																	

○ Good ⊕ Best

